

JAN 22 2001

SECTION

2000 REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

00 DEC -1 AM 9:33

LIDER NO. 3 PAGE NO. 76
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

For corners in

Sanilac Located In: Corner Code #
(County)

1. Public Land Survey T11N R16E D - 7
T R
T R
T R

2. Property Controlling S T R
in Section S T R

3. Miscellaneous S T R
Property in Sec. S T R

Register of Deeds Stamp & File Number

1. Lot No. , Recorded Plat
2. Private Claims

2000
John A Millettics, in a field survey on May 1, 2000, do hereby state that under
equirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in
onformance with regulations and rules therefore as required in the current manual of survey instructions of the
United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or
at the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan
oard of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented,
covered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

Description of original monument and accessories and/or subsequent restoration:

D - 7

S 1/4 Corner Section 17 T11N-R16E

GLO Notes

Sugar Maple 24" South 25 Links

White Ash 13" N33°E 28 Links

Act 132 - None

Unrecorded surveys - Millettics Oct 1995- Millettics Dec 1997 - Millettics Dec 1999

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D - 7

S 1/4 Corner Section 17 T11N-R16E

Found 1/2" Iron Bar in Gravel Road Bed

West 2657.68 feet to the SW Corner Section 17

East 2664.04 feet to the SE Corner Section 17

Accepted as best evidence



Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D - 7

S 1/4 Corner Section 17 T11N-R16E

1/2" Iron Bar in Gravel Road Bed

South 33.00 feet to a 1/2" Iron bar with cap

S40°E 56.20 feet to a nail in a 6" Crab apple tree

S30°W 39.95 feet to a nail in a 6" Ash tree

N10°E 34.35 feet to a nail in a 10" Ash tree

S60°E 69.50 feet to a nail in a 6" Crab apple tree

West 2657.68 feet to the SW Corner Section 17

East 2664.04 feet to the SE Corner Section 17

APPROVED PEER BOARD
MEETING NOV 25 2000

gm

igned by John A Millettics

Date Nov 15, 2000

urveyor's Michigan License No. 25859