

SEP 20 2000

SECTION

LIBER 3 PAGE 1

2000 REMONUMENTATION PROGRAM
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED FOR RECORD

00 JUN 13 AM 11:56

For corners in

Sanilac
(County)

Located In:

Corner Code #

LIBER NO. 3 PAGE NO. 4
MICHELE VANORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

1. Public Land Survey

T12N R15E F - 7

2. Property Controlling
in Section

S
S

T
T

3. Miscellaneous
Property in Sec.

S
S

T
T

*Should be
R14E not
=
R15E pm*

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

2000

I, John A Milletics, in a field survey on March 29, 1998 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

F - 7 GLO Notes

Black Ash 9" S55°W 10 Links

Black Ash 10"N16°E 18 Links

OLD Survey Liber - M.E. Ward Dec. 1896 - Thomas Nicol May 1902

Act 132 - None

L.C.R.C. - None

Unrecorded Surveys Dated - Milletics April 1986, Milletics Jan. 1991
Milletics Oct. 1994

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F - 7 S 1/4 Corner Section 16

Found 1/2" Iron in Gravel Road Bed

West 2657.48 feet to the SW Corner Section 16

East 2657.48 feet to the SE Corner Section 16

Accepted as best evidence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F - 7

S 1/4 Corner Section 16 T12N-R14E

1/2" Iron Bar with cap in gravel Road Bed

South 32.85 feet to a 1/2" Iron Bar

S10°E 18.70 feet to a nail in a 30" Ash

S45°W 76.80 feet to a nail in a 24" Ash

S75°E 84.50 feet to a nail in a 24" Ash

West 2657.48 feet to the SW Corner Section 16

East 2657.48 feet to the SE Corner Section 16

APPROVED PEER BOARD
MEETING JUNE 12, 2000

Signed by

John A Milletics

Date April 11, 2000

Surveyor's Michigan License No. 25859