

JAN 22 2001

LIBER

3 PAGE 61

RECEIVED FOR RECORD

00 NOV 29 AM 11:11

LIBER NO. 3 PAGE NO. 61
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

SECTION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970
2000 REMONUMENTATION PROGRAM

For corners in

Sanilac

(County)

Located in:

Corner Code #

1. Public Land Survey

T12N R16E F - 13

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

2000

I, John A. Millettics, in a field survey on May 1, ~~199~~ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO Notes

Black Ash 15" N13°W 18.5 Links

Cedar 7" N73°E 32 Links

ACT 132 - None

Unrecorded Surveys - Sanilac Land Survey June 1980, Millettics Jan 1999 & Oct 1999

L.C.R.C. - None

Old Survey Liber - None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

F - 13

S 1/4 Corner Section 33 T12N-R16E

Found no evidence of corner on site

Removed by State Highway Department during construction

West 2652.60 feet to the SW Corner Section 33

East 2644.56 feet to the SE Corner Section 33

Accepted as best evidence

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

F - 13

S 1/4 Corner Section 33 T12N-R16E

1/2" Iron Bar with cap in concrete

North 1.30 feet to the centerline of M- 46

East 24.00 feet to the N 1/4 Corner Section 4

North 60.00 to the Face of a Buried Cable Sign

N10°E 57.40 feet to a nail in a Power Pole

S20°E 62.30 feet to a nail in a Power Pole

N75°E 132.6 feet to a nail in a 24" Maple

West 2652.60 feet to the SW Cor. Sec. 33 - East 2644.56 feet to the SE Cor. Sec. 33

Signed by John A. Millettics

Surveyor's Michigan License No. 25859

Date Nov 15, 2000

APPROVED PEER BOARD
MEETING Nov 25, 2000

SM