

JAN 22 2001

LIBER

3 PAGE 47

SECTION

2000 Remonumentation Program
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Sanilac

(County)

Located in:

Corner Code #

1. Public Land Survey

T12N R16E

G - 7

T R

T R

T R

T R

2. Property Controlling in Section

S

T R

S

T R

3. Miscellaneous Property in Sec.

S

T R

S

T R

RECEIVED FOR RECORD

00 NOV 27 AM 8:56

LIBER NO. 3 PAGE NO. 47
MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

John A. Milletics, in a field survey on May 1, 2000, do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and for that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below.

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO Notes

Hemlock 10" S03°W 12 Links

Hemlock 9" N21°E 21 Links

Act 132 = Liber 3 Page 240

L.C.R.C. Forms - None

Unrecorded surveys - Milletics Aug 1990, Milletics July 1995, Milletics Oct 1998

3. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G - 7

SE Corner Section 16 T12N-R16E

Found 1/2" x 3" x 24" Bar in gravel road bed

West 2611.08 feet to the S 1/4 Corner

East 2638.74 feet to the S 1/4 Corner

Accepted as best evidence

2. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G - 7

SE Corner Section 16 T12N-R16E

1/2" x 3" x 24" Iron bar in gravel road bed

N45°W 75.70 feet to a nail in a 24" Pine

N20°W 34.25 feet to a Stop Sign

N30°E 36.65 feet to a nail in a 36" Tree Stump

S30°E 35.10 feet to a Stop Sign

West 2611.08 feet to the S 1/4 Corner

East 2638.74 feet to the S 1/4 Corner

APPROVED PEER BOARD
MEETING NOV 25 2000

Signed by John A. MilleticsDate Nov 15, 2000Surveyor's Michigan License No. 25859