

RECEIVED FOR RECORD

98 DEC -1 AM 9:09

LIBER NO. 2 PAGE NO. 257

MICHELE VANNORMAN
REGISTER OF DEEDS
SANILAC CO., MICHIGAN

REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Sanilac
(County)

Located In:

Corner Code #

1. Public Land Survey		T14N R15E	M-13
		T R	
		T R	
		T R	
2. Property Controlling in Section	S	T R	
	S	T R	
3. Miscellaneous Property in Sec.	S	T R	
	S	T R	

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims

I, John A. Millettics, in a field survey on Oct 20, 19 98 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A	B	C	D	E	F	G	H	I	J	K	L	M
1												
2	6		5		4		3		2		1	
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

A. Description of original monument and accessories and/or subsequent restoration:

M-13 GLO Notes - Hemlock 18 S66W 48; Beech 12 N15E 21;
Beech 12 N65 1/2W 41; Beech 12 N15E 21;
Hemlock 24 S55W 42 1/2; Hemlock 18 S66W 48
Old Survey Liber - Survey by M.E. Ward dated 1891
L.C.R.C. - None
Act 132 - None
Road Comm - None

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

M - 13
SE Corner Section 36 T14N-R15E
Found 1/2" Iron Bar
Accepted as best evidence

SURVEY &
REMONUMENTATION

JAN 15 1999

SECTION



APPROVED PEER BOARD MEETING
NOV 30, 1998

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M - 13
SE Corner Section 36 T14N-R15E
1/2" Iron bar
West 2643.82 feet to the S 1/4 Corner Section 36
East 2640.10 feet to the S 1/4 Corner Section 31
N45°E 78.50 feet to a nail in a Power Pole
N40°E 52.00 feet to the East End of a CMP
N40°W 47.30 feet to the West End of a CMP
N45°W 40.90 to a Bell Box

Signed by John A. Millettics
Surveyor's Michigan License No. 25859

Date Nov 20, 1998