SURVEY & REMONUMENTATION

ST. CLAIR COUNTY, MICHIGAN OFFICIAL GOVERNMENT CORNER

LAND CORNER RECORDATION CERTIFICATE

MAR 1 6 1999	Filing Requirement	of Act 74, Mich. P.A. 1970) REC
SECTION	Located In:	Corner Code #	
1. Public Land Survey	T 5N R 17E	Supplemental	185 = 28
 Property Controlling S in Section S Miscellaneous S Property in Sec. S 	TR TR TR TR	# 2-	1 NES 15
1 Topolty III 200.			Register of Deeds Stamp & File Number
4. Lot. No, F 5. Private Claims on No			A B C D E F G H I J K L M
1970, the corner points me with regulations and rules instructions of the United Management or by a dec mentioned in lines 3, 4 an Michigan Board of Land	hat under requirements of the entioned in lines 1 and 2 therefore as required in the States Department of the entire of a Court of Law and 5 above were in conformal Surveyors or by a D	of P.A. 74, Michigan P.A. of above were in conformance the current manual of survey the Interior, Bureau of Land and/or that the corner points remance with the rules of the ecree of a Court of Law;	2 6 5 4 3 2 1 1 3 4 7 8 9 10 11 12 5 6 15 14 13 7 8 19 20 21 22 23 24 9 10 30 29 28 27 26 25 11 2 31 32 33 34 35 36
NOTE: Not more than 1	CORNER, may be reco	rded on this certificate.	13
A. Description of original monument and accessories and/or subsequent restoration:			
intersects the north line of on Old County Surveyors monumentation. J. Lansk J. Lansky . May 1974. lists	f Private Claim No. 305 at Record. Glen Whitmore by, December 1971, record corner in recorded surv	nd is common to supplement survey dated August 1952 re vers and records a monumen	m Preston in 1817. This corner ral corner of T5N-R16E. Nothing listed ferences corner but does not list type of it box, see LCRC Liber 1, page 98. Dely, December 1987, lists corner in see Liber 16, page 676.
B. Description of corner e	evidence found and/or m	ethod applied in restoring or	reestablishing corner:
Verified corner using prev Ketchum Road 1108.16' (riously recorded witnesse M) and 1108.10' (R). Alse	es. Also checked distances li	section of Range Road and Brown Street. sted on surveys; North to PK nail at I-R17E, 2283.88' (M) and 2283.67' (R) 61' (M) and 88.45' (R)
C. Description of monum	ent for corner and acces	sories established to perpetu	ate locating the position of the corner:
diameter rerod located in lies on the north line of Pr East 88.61' to cen NE 63.89' to cent NW 79.63' to PK r NE 97.97' to PK n SE 75.38' to PK n SW 58.33' to PK r	the existing monument be ivate Claim No. 305. Interline of CSX Railroad Terror for nut of fire hydramail with SCC Remon was all with SCC Remon was all with SCC Remon was	oox at the centerline of Range racks	C. 15, 1998
Signed by	- New Course	14608	Date <u>Plecember 28, 1998</u>
Surveyor's Michigan Lise	nse No2	24608	BOOK 009 PAGE 243