

SURVEY &
REMONUMENTATION

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

LIBER 4 PAGE 70

For corners in

ST. JOSEPH
(County)

Located In:

Corner Code =#

PARK TOWNSHIP

1. Public Land Survey

T 5S R 11W

C-10

T R

T R

T R

T R

2. Property Controlling
in Section

S T R

S T R

3. Miscellaneous
Property in Sec.

S T R

S T R

STATE OF MICHIGAN
ST. JOSEPH COUNTY
FILED

6 DEC 94 4:30 P.M.

CYNTHIA JARRATT
REGISTER OF DEEDS
Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, DAVID W. MOSTROM, in a field survey on OCTOBER 7, 1994, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(C-10) 1/4 CORNER COMMON TO SECTIONS 29 & 30

GLO-POST

1878 - BOOK A, PG. 28

7" W. OAK = N60°E 32 LINKS

STAKE FROM OLD BRG TREES

7" W. OAK = S88°W 45 LINKS

NO WITNESSES

1866-BOOK A, P-146

1955 - JAY WHITE SURVEY

CORNER NOT LABELED

STONE UNDER POST
NO WITNESSES

1992 - LCRC IN BOOK 3, PG. 227 &
MOSTROM SURVEY #9722

FOUND OLD STONE PER JAY WHITE SURVEY
LEANING - RESET 3/4" X 24" PIPE USING
TIES TO CORNERS ON SURVEY TO NORTH
F. POST = NORTH 6.85' 1" HICKORY =
S85°E 25.5'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(C-10)

F. POST = NORTH 15.48' TREE = N80°E
31.21'
OLD IRON FD. = NORTH 524'

FOUND 3/4" X 24" PIPE IN CIRCLE OF
STONES IN PROJ. OF N-S FENCE & AT S. EDGE OF WOODS
F. POST = NORTH 6.85'
F. POST = NORTH 15.48'
3" HICKORY = S85°E 25.5'
6" HICKORY = N80°E 31.21'
OLD IRON FOUND = NORTH 524'

RATIFIED BY PEER GROUP
IN ACCORDANCE WITH P.A. 345
ON NOV. 14, 1994
Wm CO. REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(C-10)

SET 5/8" X 24" IRON W/STD. CAP IN CIRCLE OF STONES
PK NAIL & TAG 2' HIGH ON W. SIDE OF R.R. TIE POST = NORTH 15.48'
PK NAIL & TAG 1' HIGH ON W. SIDE OF R.R. TIE POST = NORTH 6.85'
PK NAIL & TAG 2' HIGH ON S. SIDE OF 3" HICKORY = S85°E 25.40'
PK NAIL & TAG 4' HIGH ON S. SIDE OF 6" HICKORY = N80°E 31.21'
CORNER FALLS IN PROJ. TO FENCE TO NORTH & ON S. EDGE OF WOODS



Signed by

David W. Mostrom

Date

NOV. 17, 1994

Surveyor's Michigan License No.

32339

REMONUMENTATION