DEC 01 1998

LIBER 5 PAGE 90

STATE OF HICHIGAN

SECTION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74 Mich

ST.	JOSEPH	COUNTY
	FILED	

For corners in	•	redunctions of Mot 14 9	/iicit. P.A. 1970	29 JU 1998	11:09:59 AM
St. Joseph (County) Flowerfield Twp. 1. Public Land Survey	Located In: T 5S R 12 T R T R	Corner Code #		CYNTHIA I	L. JARRATT OF DEEDS
2. Property Controlling in Section 3. Miscellaneous Property in Sec.	TR STR STR STR		Reg	lister of Deeds S	itamp & File Numb
4. Lot No, Recorded	l Plat	•			
5. Private Claims i,David_WMostrom_, in requirements of P.A. 74, Michigan P./. conformance with regulations and rules United States Department of the Interior that the corner points mentioned in line Board of Land Surveyors or by a Direcovered, found as expressed below: NOTE: Not more than 2 comers, a on this certificate.	a field survey on	5/13, 19 98 do hereby sta ints mentioned in lines 1 and 2 a the current manual of survey instru- tement or by a decree of a Court of in conformance with the rules of the w, established, re-established, m	bove were in actions of the flaw and for 6 18	C D E F	G H I J K
A. Description of original monume	ent and coordanies and	ر بالدالية	13		
A Description of original monumes 1886 Survey in A/538 Stk. & over it a stone NE Cor. of Hse. upright 119 lks. (78.54') SE Cor. of Hse. upright 585°W 118 Lks.	Road Com Pipe dri of stk. a Mon. Box 11" Maple SE Cor. s	wen thru remains under stone in e = \$73°W 50.7' shed = N18°W 89.7'	Pierce 1977 Gove Survey Iron rod in N 1997 LCRC in Fd. 3/4" pipe NE Cor. Hse. SE Cor. Hse.	Mon. Box 4/323 over sto. = N83°W 78 = S85°W 77	in Mon. Box
3. Description of corner evidence	found and/or method:	applied in restoring or reestab	14" Wal. = N2 Dishing corner: 10" M	!5°W 89.92° Na1. = N45°¥	, J 44 56'
The 1 2 (4 H			-		, 22.50

Found 3/4" x 10" pipe over sto. 12" deep in Mon. Box CL Flatbush Road is 1' W. Of Cor. NE Cor. Hse. = N83°W 78.54

38" Maple = S73°W 50.7

All points are in OK from 1997 LCRC

RATIFIED BY PEER GROUP IN ACCORDANCE WITH P.A. 345 July 13 . 1998 u CO. REPRESENTATIVE ON

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner.

Set 5/8" x 9" Bar in Conc. w/std. cap over stone in Mon. Box

N & W in E. side 14" Wal. = N25°W 89.92'

N & W in NW side 10" Wal. = N45°E 44.56'

N & W in N. side 38" Maple = S73°W NE Cor. Metal Bldg. = N60°W 117.74'

NE Cor. Fdtn. of old Hse. = N83°W 78.45

Signed by Surveyor's Michigan License No. 14100

7/28/98 Date

