

SURVEY &  
REMONUMENTATION

NOV 30 1993

004 PG 010

FILED

COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

corners in

ST. JOSEPH  
(County)

Located In:

Corner Code #

FLOWERFIELD TWP.  
Public Land Survey

T 5 S R 12 W

I-9

T R

T R

T R

Property Controlling

S T R

in Section

S T R

Miscellaneous

S T R

Property in Sec.

S T R

JUL 27 1 02 PM '93

Cynthia L. Janett  
REGISTER OF DEEDS  
ST. JOSEPH CO MICH

Register of Deeds Stamp & File Number

Lot No. , Recorded Plat

Private Claims

WAYNE A. MOSTROM, in a field survey on JULY 9, 1993, hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as pressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

2  
" W.O. S59½°E 35 LKS  
" W.O. N25 3/4°W 53 LKS

ROAD COMM.-1962

88 SURVEY BY TODD (A/597)

DUG W/MOTOR GRADER-FOUND NOTHING

OLD NOT FIND ORIG. COR-

REPRODUCED OLD MAPLE WIT. TREE (OUT) BY EXT. TREE ROW TO W&S-  
VERIFIED LOC. BY TESTIMONY OF 2 LOCALS- SET PIPE IN MON BOX

SET BY PROP. DIST'S FRM

L.C.R.C. (3/37) 1977

R'S ½ MI IN ALL DIR.

MAPLE = S45° 47 3/4 LKS

T STAKE/STONE

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FD. PIPE IN MON BOX

20" MAPLE = N61°E 47'

IRON ANCHOR POST = S47°W 38.5'

24" MAPLE = S66°W 55'

(SAME WITNESSES)

10" MAPLE = N61°E 47'

A.P. = S47°W 38.5'

23" MAPLE = S66°W 55'

Description of monument for corner and accessories established to perpetuate locating the position of

SET 5/8" X 24" BAR & STD. CAP. IN MON BOX

N&W IN SE SIDE 20" MAPLE = N61°E 47.0'

N&W IN N SIDE 20" HICK. = S75°E 97.50'

☉ OF IRON ANCHOR POST = S47°W 38.50'

N&W IN N. SIDE 24" MAPLE = S66°W 55.0'

COR IN IN ☉ E-W RDWY & 2' W OF ☉ N-S RDWY

WITNESS NAILS IN TREES ARE 24" HIGH



APPROVED BY PEER GROUP 7/12/93 AS ACCEPTED RE-ESTABLISHMENT OF ORIGINAL CORNER

igned by *Wayne A. Mostrom*

Date 7/16/93

urveyor's Michigan License No. 14100