

NOV 11 1997

COMMITTEE

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

ST. JOSEPH

(County)

COLON TWP.

1. Public Land Survey

Located In:

Corner Code #

T6S R 9W

D-5

T R

T R

T R

T R

2. Property Controlling
in Section

S

T R

S

T R

3. Miscellaneous
Property in Sec.

S

T R

S

T R

LIBER 5 PAGE 27

STATE OF MICHIGAN
ST. JOSEPH COUNTY
FILED

22 SEP 97 3:26 P.M.

CYNTHIA JARRATT
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, WAYNE A. MOSTROM, in a field survey on AUGUST 3, 1997 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO

14 W.O. = N44°E 8 LKS

20" Y.O. = S29½°W 13 LKS

L.C.R.C. - 3/42 - 1974

FOUND STONE

PK IN E SIDE POLE = S 22.42'

6" MAPLE = NE 51.23'

1974 SURVEY BY SAYERS

PK IN E SIDE POLE = SOUTH 22.42'

6" MAPLE = NE 51.23'

PK IN STOP SIGN = NW 48.23'

1886 SURVEY BY TODD

BOOK A, PAGE 494

SET R.O. POST 4"X36" ON MILE SPLIT

14" WALNUT = N60°E 67 LKS

12" HICKORY = N73 3/4°W 1.29 CH

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

RR SPIDE OVER STONE OVER 1 1/4" PIPE

MAPLE = NE 51.23'

PK IN SOUTH SIDE POLE = SOUTH 22.42'

1976 SURVEY BY MOSTROM

FOUND STONE

6" MAPLE = NE 51.23'

STOP SIGN = NW 48.23'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 5/8" X 24" BAR W/STD. CAP IN MON. BOX IN GRAVEL RDWY.

COR. IS IN APPROX. C OF E-W RD.

N & W IN EAST SIDE P.P. = S20°W 22.45'

C OF STREET SIGN = S60°W 24.00'

1/2" X 18" IRON BAR = N50°W 59.13'

MAG. NAIL IN PVM'T (5'± E. OF STOP SIGN) = N20°W 47.84'

RATIFIED BY PEER GROUP
IN ACCORDANCE WITH P.A. 345
ON SEPT 8, 1997
Wayne A. Mostrom CO. REPRESENTATIVE



Signed by Wayne A. Mostrom WAYNE A. MOSTROM

Date AUGUST 20, 1997

Surveyor's Michigan License No. 14100