LAND CORNER RECORDATION CERTIFICATE PAGE 28 Filing Requirement of Act 74, Mich. P.A. 1970 IER For corners in STATE OF MICHIGAN St. Joseph ST. JOSEPH COUNTY Located in: Corner Code # FILED Lockport Twp. 1. Public Land Survey T6S R 11W E-3 29 MAR 2000 10:15:53 AM R CYNTHIA L. JARRATT REGISTER OF DEEDS 2. Property Controlling **EMONUMENTATION** in Section 3. Miscellaneous Property in Sec. IAN <u>31 200</u>1 Register of Deeds Stamp & File Number , Recorded Plat SECTION 5. Private Claims 2 3 Wayne A. Mostrom, in a field survey on Sept. 8 \_, 19 $\frac{99}{}$  do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the 5 United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan 6 Board of Land Surveyors or by a Decree of a Court of Law, established, re-established, monumented, 7 recovered, found as expressed below: 8 NOTE: Not more than 2 corners, all in the same town and range, may be recorded 9 on this certificate. 1: 12 A. Description of original monument and accessories and/or subsequent restoration: Sayers 1971 Survey Sayers 1975 Survey Sayers Witness Book LCRC in 2/34 (1975) Triangular Shaped Long Split Blue-Green Grooved Sto 6\* deep Split Stone & Bolt Found Blue Stone Stone with Bolt in top 30" Elm SE 41.4' P.P. = NE 47.95' Locust Stump = W 23.4' NW face of twin of Stone 6" Oak = SW 25.4" 10" Locust = SW 54.23' P.P. = NE 47.94' P.P. = NE 47.941 20" Elm = NW 33' 10" Locust = SW 54.2' 10" Locust = SW 54.2" 16" Locust = N 35.11 Post = N 33' 6" Oak = SW 25.4" Mostrom 1994 Survey Fd Stone & Bolt over it B. Description of corner evidence found and/or method applied in restoring or reestablishing corner: Found Blue Triangular shaped split stone 7" deep with several pieces of iron over it (horizontal). Corner is in gravel drive to North and in proj. of Asphalt Roadway to West and South. 10" Locust (now a stump) = SW 54.23', P.P. = NE 47.94' Post = N. 33' 6" Oak = SW 25.41 RATIFIED BY PEER GROUP IN ACCORDANCE WITH P.A. 345 ON Sept. 13, 1999 Muy CO. REPRESENTATIVE C. Description of monument for corner and accessories established to perpetuate locating the position of the corner: Replaced Stone with 5/8" x 24" Iron w/std. cap WITHIN OF MICHIGAN W in N. Side 14" Oak = \$85°W 25.20' SATE OF MICH OF WAYNE A & W in N. Side P.P. = N45°E 48.26' N & W in S. Side 18" Locust = West 42.59' N & W in E. Side 6" Anchor Post = North 33.04' N & W in E. Side 36" Twin Elm = S40°E 89.20' **WAYNE** A **MOSTROM** ROFESSIONAL SURVEYOR No. 14100 POFESSIONA S ESSION Wavne A. Mostrom Date #14100 Surveyor's Michigan License No.