

ST JOSEPH

## LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY <u>20</u> T. <u>6</u> S., R. <u>12</u> W.		D-7, D-8
2. PROPERTY CONTROLLING IN SECTION _____, T. _____ S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION _____, T. _____ S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Donald L. Bissell, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on May, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

D-7 Found 1" square iron by measurements from Clear View Shores Subdivision.

D-8 Found 1/2" pipe by measurements from Schellhaus Subdivision.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-7 1" Square Iron w/plastic cap.  
North, 5.00', 20" Sassafrass, Spike and Tag  
N 75° E, 3.46', 16" Sassafrass, Spike and Tag  
S 40° E, 31.36', 15" Cottonwood, Spike and Tag  
S 86° W, 6.24', 3" W. Oak, Spike and Tag

D-8 1/2" Pipe w/plastic cap.  
N 46° W, 4.33', Power Pole, Spike and Tag  
N 63° E, 65.30', 12" Ash, Spike and Tag  
S 6° E, 41.29', 18" Hickory, Spike (Old W  
S 42° W, 51.83', 18" Hickory, Spike (Old W  
N 63° E, 29', C Road  
N 28° W, 26', E Drive

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY \_\_\_\_\_ DATE \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 18655

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971  
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET