

SURVEY &  
REMONUMENTATION  
APR 10 1995  
COMMISSION

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970  
4 PAGE 72

ST. JOSEPH  
(County)  
BURR OAK TWP.

Located In:

Corner Code #

STATE OF MICHIGAN  
ST. JOSEPH COUNTY  
FILED

6 DEC 94 4:30 P.M.

CYNTHIA JARRATT  
REGISTER OF DEEDS

Register of Deeds Stamp & File Number

1. Public Land Survey T 7 S R 9 W G-4  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_  
T \_\_\_\_\_ R \_\_\_\_\_
2. Property Controlling S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
in Section S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
3. Miscellaneous S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_  
Property in Sec. S \_\_\_\_\_ T \_\_\_\_\_ R \_\_\_\_\_
4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_
5. Private Claims \_\_\_\_\_

	A	B	C	D	E	F	G	H	I	J	K	L
2	6		5		4		3		2			
3												
4	7		8		9		10		11		12	
5												
6	18		17		16		15		14		13	
7												
8	19		20		21		22		23		24	
9												
10	30		29		28		27		26		25	
11												
12	31		32		33		34		35		36	
13												

I, WAYNE A. MOSTROM, in a field survey on NOVEMBER 10, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

**NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.**

A. Description of original monument and accessories and/or subsequent restoration:

G-4

1873 SURVEY BY GARDNER  
"STONE SET FROM ORIGINAL  
BEARING TREE, NOW GREEN"

COUNTY ROAD COMM. IN 1963

LARGE POINTED STONE UNDER  
MONUMENT BOX  
P. POLE = S67°W 76.35'  
ANCHOR POST = S53°E 43.85'

LCRC IN L-3, P-96 DATED 1975

FOUND STONE IN MON. BOX  
IRON POST = N45°W 29.6'  
ANCHOR POST = S45°W 34.5'  
TELE. POLE = SE 52.11'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-4

FOUND POINTED STONE IN MON. BOX  
ANCHOR POST = S45°W 34.50'

RATIFIED BY PEER GROUP  
IN ACCORDANCE WITH P.A. 345  
ON 8/8, 1994  
Wayne A. Mostrom CO. REPRESENTATIVE

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-4 (1/4 COR. BETWEEN SECTIONS 9 & 10)

SET 5/8" X 24" BAR IN PLACE OF STONE WITH STD. CAP IN MON. BOX  
N & W IN POWER POLE = S67°W 76.90'  
N & W IN NEW ANCHOR POST = S45°E 49.28'  
1/2" IRON BAR = S45°W 40.00'  
1/2" IRON BAR = N45°E 40.00'  
E OF EXIST. RDWY'S ARE 4' SOUTH & 2' EAST OF COR.



Signed by Wayne A. Mostrom

Date 11/11/94

Surveyor's Michigan License No. 14100

REMONUMENTATION