SCHOOLCRAFT COUNTY PEER GROUP APPROVED

JAN 21 1999

ח	Δ	rF	10/21	198	JUB
	~		10/6	, , ,	V - 1/

Surveyor's Michigan License No. 21274

DATE 10/21/9	8 JOBS	CORNER RECORD		SECTION	
For corners in	Filing	CORNER RECORDA g Requirement of Act	TION CERTIFIC 74, Mich. P.A. 19	ATE 970	
Schoolcraft (County)	Located In:	Corner Code#			
Public Land Survey Property Controlling in Section Miscellaneous Property in Sec.	T41NR1 TR_ TR_ S TR_ S TR_ S TR_ S TR_		SIGRID H SC Page 1 o JLV Rec REVENUE		
4. Lot No, Record	ded Plat		<u></u>	Register of Deeds Stamp & File Number	er_
IThomas P.O'Brien requirements of P.A. 74, Michigan conformance with regulations and r United States Department of the In that the corner points mentioned in Board of Land Surveyors or by recovered, found as expressed belo	in a field survey on Och P.A. of 1970, the corner rules therefore as required the increase of a Court of a Decree of a Court of	ct. 23, 19 98 do her points mentioned in lines 1 a in the current manual of survenagement by a decree of a care in conformation with the current manual of survenagement of the conformation with the current conformation wit	eby state that under ind 2 above were in y instructions of the Court of Law and /or	1 A B C D E F G H I J K 2 6 5 4 3 2 3 4 7 8 9 10 11 1 5 5 6 18 17 16 15 14 1	L M
NOTE: Not more than 2 come on this certificate.		and range, may be recorder	d	8 19 20 21 22 23 2 9 10 30 29 28 27 26 2 11 12 31 32 33 34 35 3	5
A Description of original months C8 W & Corner Sec Sept. 15, 1849 Beech 8 N 6 E 40	5 - John Burt	D.S. set ar	ration: section po	est referenced by:	
March 18 & 19	, 1982 - LCR	C by David B.	Babbitt (L.	.1, Pg. 287 RLS 21558).	
		ary E. Koepke			
11df C11 27, 199	J - LCKC by (seraid w. Cari	son (L.4 Pg	g. 168 P.S. 24589).	
B. Description of corner evide					
C8 Oct. 23, 1998 Box on the East s BT varifies locat	snoulder of M	-149. centerli	ne 13.80 fa	d "T" iron in Monument eet West. One remaining	
C. Description of monument for C8 "T" Iron in Mo the following ref	nument Box o	es established to perpetuat n East gravel	e locating the positi shoulder o	on of the corner: f M-149. Established	
(Fd.) Power Pole NBT 18" Ash - N NBT 6" Tamarac NBT 4" Cedar Centerline of R Carsonite post-	38°W - 173.8 k - N58°E - 1 - S74°E - 100 /R tracks - 1 East = 15.0'	7' 39.65' 6.45'	Date: N-	THOMAS P. O'BRIEN PROFESSIONAL SURVEYOR NO. 21274 POFESSIONAL OVERDER 231111 1998	
			Date No	/Vember Z31 1998	