

SCHOOLCRAFT COUNTY  
PEER GROUP APPROVED

DATE 10/10/00 JLB LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

SURVEY &  
REMONUMENTATION

FEB 08 2001

For corners in

Schoolcraft  
(County)

Located in:

Corner Code #

SECTION

1. Public Land Survey

T 42N R 13W

A9

T R

T R

T R

T R

T R

T R

T R

2. Property Controlling  
in Section

S

T R

S

T R

3. Miscellaneous  
Property in Sec.

S

T R

S

T R

SIGRID HEDBERG 1P  
SCHOOLCRAFT CO. REGISTER  
Page 1 of 1 LC 4/408  
JLV Date 12/28/2000 Time 11:27:40

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, Thomas P. O'Brien, in a field survey on 11/27/00 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

1850 Guy H. Carleton DS set post Cor to SEct. 24 and 25 (42N-14W)  
Cedar 14 N31E 47 Spruce 8 S27E 47 Cedar 14 S59W 23 YBirch 18 N40W 14

March 1984 William F. Bowman LLS " set by proportionate measure on line between  
M7 (42-14) and M9 (42-14)."

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Nov.27, 2000 Thomas P. O'Brien PS found 1" pipe with 4" Mead cap and LS 28406 stamp  
as set by Bowman.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

1" pipe with 4" Mead cap stamped to identify.

Witnesses:

8" Mtn. Ash N62°E 10.75'

6" Mtn. Ash S73°E 27.95'

8" Mtn. Ash N80°W 21.60'

4" Mtn. Ash N5°E 28.35'

Carsonite Post North 1.0'



Signed by Thomas P. O'Brien

Date Dec.28, 2000

Surveyor's Michigan License No. 21274