## SCHOOLCKAFT COUNTY PEER GROUP APPROVED

SURVEY & REMONUMENTATION

ELIN ONOOI MITNOVID	007
DATE Manch 10, 1995 AND CORNER RECORDATION CERTIFIC	OCT 2 6 1995
For corners in Filing Requirement of Act 74, Mich. P.A.	1970 COMMISSION
Schoolcraft Located In: Corner Code ##	
1. Public Land Survey 1 42N R 15W F13 -	Received & Filed this 10 day of March 1995 at 2:30 pM
	Sigrid I. Hedberg Schoolcraft Co. Reg. of Deeds  Register of Deeds Stamp & File Number
4. Lot No, Recorded Plat	
5. Private Claims	A B C D E F G H I J K L
do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentione in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Lan Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of Court of Law; established, re-established, monumented, re-monumented, recovered, found a expressed below:  NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.  A. Description of original monument and accessories and/or subsequent restoration: F-1 (North 1/4 Corner Sec.4)  Oct.25, 1841 William A. Burt, D.S set qr. section Beech 6 N23E 41 Birch 12 N60W 32	18 17 16 15 14 13 5 8 19 20 21 22 23 24 a 10 30 29 28 27 26 25 11 12 31 32 33 34 35 36

- B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
- F-1 Sept.17, 1964 Arthur O. Enger. RLS recovered pipe set by Carl Christensen, presumably from original bearing trees or personal knowledge of corner's history. Road construction has destroyed any evidence of BT's. Corner seems to check well with natural features and other corners eastward along the township line.

Nov.24, 1993 - Thomas P.O'Brien, PS recovered Carl Christensen monument.

- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
- F-1 2" iron pipe w/2 1/2" brass cap stamped "33-1/4-4, C.C."
  16" Jack Pine N22 1/2W 96 1/2 links (63.69') Enger witness.
  10" White Pine S65W 82 links (54.12') Enger witness.
  6" Red Pine S89E 99.80'(NBT)

12" Maple S33W 49.65' (NBT)

LIBER 2 PAGE: 38 1

\_ Date \_

March

Thomas P.O'Brien, PS 21274 Surveyor's Michigan License No. \_\_