

SCHOOLCRAFT COUNTY  
PEER GROUP APPROVED

DATE 7/12/96 JOINT CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Schoolcraft Located In: Corner Code #  
(County)

1. Public Land Survey T42NR15W G-10  
T R  
T R  
T R

2. Property Controlling S T R  
in Section S T R

3. Miscellaneous S T R  
Property in Sec. S T R

Received & Filed this 8th day of  
October 1996 at 11:30 AM  
Sigrid I. Hedberg  
Schoolcraft Co. Reg. of Deeds

Register of Deeds Stamp & File Number

4. Lot No. \_\_\_\_\_, Recorded Plat \_\_\_\_\_  
5. Private Claims \_\_\_\_\_

I, Thomas P. O'Brien, in a field survey on Aug. 14, 1996 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28	X	27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:

G-10 (E 1/4 Corner of Section 28)  
Sept. 18, 1850 Algernon Merryweather D.S. set qr. section post.  
Beech 9 in. S40E 13 links Spruce 7" N10W 14"

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-10 August 14, 1996 Thomas P. O'Brien P.S. set corner by single proportionate measurement, between G-9 and G-11. Set iron bar with 21274 cap in monument box.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-10 Set iron bar with #21274 cap in monument box.

Witnesses: Power Pole - N50°E - 60.90'  
Service Pole - S70°E - 147.55'  
6" Maple - S58°W - 56.08'  
M.B.T. Pole - N23°W - 72.76'  
4" Cedar post - West - 33.0'

Signed by Thomas P. O'Brien  
Surveyor's Michigan License No. 21274

Date August 14, 1996

