CINTY REMONUMENTATION

SCHOOLCRAFT COUNTY PEER GROUP APPROVED

LAND CORNER RECORDATION CERTIFICATE

Very	2	م ب	1996
4/% 414			3000

(East 1/4 Corner Sec. 12)

DATE 9/13/96 Filing Requirement of Act 74, Mich. P.A. 1970

FU	or corners in																
S	choolcraft (County)	Located In:				Corner Code ##		įved									
1.	Public Land Survey		т <u>42.</u>] Т	N R 15 W N R 14 W — R	-	M-4 V	Sigri	d (. H olcra	edb	erg			 -		_£	! M	
2.	Property Controlling		T	R	_												
	in Section	S _	T	R	-												
3.		s	T	R	_		Be	egister	of D	eeds	Star	nn &	File	Mir	mhe	.	
	Property in Sec.	s _	T	R	-		L									<u>. </u>	
4.	Lot No,	Recorde	ed Plat														
5.	Private Claims							- A	В	C D	_ E	F G	Н.	1 1	K	L	М
								_ 2	- 6	- J	Щ.	4-	_ 3 _	1-!	<u> </u>	<u> </u>	_
								3				\Box	Ĺ			LĹ	
								4	_	_							
1, T	homas P.O'Brien_	, in a fi	ield survey	onAp	ril	_3	16	5		ľ	T	íΤ	i I	T	iΠ	سم ا ا	7
do	hereby certify that under re	quiremer	nts of P.A. 74	4, Michigan P	A. of 1	970, the corner points me	entioned	٦			1						
in	lines 1 and 2 above were i	n confor	mance with	regulations	and n	ules therefore as require	ed in the	<u>.</u> †	-18	17. 	-+-1	6—	—15— 	+-1	4	—13- I	
Ma	rrent manual of survey instr nagement or by a decree of	a Court c	of the United	a States Dep or that the co	sartme	int of the interior, Bureau	of Land	7	1		+	1	+	+-	\vdash		_
	ove were in conformance w							8	-19	20-		1-	22	 -2	3	—2 4 -	
Co	urt of Law; established,	re-establ	lished, mor	numented, r	e-mon	numented, recovered, for	ound as	9_	+-	-		╁╌┼	+	+	┝╾┥		_
exp	pressed below:							10	-30-	29		8-	-27	ļ2	6	,—25-	4
NC	TE: Not more than 4 of	orners,	all in the	same town	and i	range, may be record	ed	11				\sqcup			\sqcup		_
	on this certificate							12	-31	_32	,		_34_				
								13	Ĺ	لَــا	L.		Ĺ			ĭ	
A.	Description of original	monum	ent and ac	cessories a	and/o	r subsequent restorat	ion:	_									

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Sept. 11/50 Algernon Merryweather D.S. set qr. section post. Ash 6 in. S80W 9 links Birch 6" N30W 32"

- Nov. 5, 1969- Frank J. Bray, RLS set a 1" pipe with 4" Aluminum cap. "Midway and on line between section corners to the North and to the South.
 - April 3, 1996- Thomas P. O'Brien P.S. recovered a 1" pipe with 4" Aluminum cap as set by Frank J. Bray on Nov. 5, 1969.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-4 Found a Dept. of Cons. 1" pipe with 4" Aluminum cap stamped to identify.

Witnesses:

M-4

Fd. 12" Red Pine- N62°E - 44 lks. Good Cond. Fd. 8" Red Pine- S37°E - 56½lks. 10" Red Pine- S 1°W - 65.20' NBT 12" Red Pine- S60°W - 20.10' NBT

4" Cedar Post - North 1.5'

_ PAGE: *_L*



Signed by Thomas P. O'Brien

Date

April 3,