SCHOOLCRAFT COUNTY PEER GROUP APPROVED

expressed below:

007 2 6 1995

CO	8 c c	
ل ا	Abr R	5

EER GROUP APPROVED

DATE March 10, 1995 LAND CORNER RECORDATION CERTIFICATE
For corners in Filing Requirement of Act 74, Mich. P.A. 1970

For corners in	Filing Requir	ement of Act 74, Mich.	P.A. 1970	
Schoolcraft (County)	Located In:	Corner Code ##	Received & Filed this 5 day of September 1995 at 11:12 AM	
Public Land Survey	T 42N R 15W T 42N R 16W T R T R	M-6 M-7	Sigrid I. Hedberg Schoolcraft Co. Reg. of Deeds	
Property Controlling in Section	S T R S T R			
Miscellaneous Property in Sec.	S T R S T R		Register of Deeds Stamp & File Number	
4. Lot No, F	Recorded Plat		A B C D E F G H I J K L M	
5. Private Claims	· · · · · · · · · · · · · · · · · · ·		2 6 5 4 3 2 3	
do hereby certify that under red in lines 1 and 2 above were it	Prin a field survey on Decquirements of P.A. 74, Michigan P.A. ronformance with regulations a suctions of the United States Depa	a of 1970, the corner points mer and rules therefore as required	ntioned 6 18 17 16 15 14 13	

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as

- A. Description of original monument and accessories and/or subsequent restoration:
- A-6 (West 1/4 Corner Sec. 18) Aug. 3, 1845 John Burt, D.S. set qr. section post. W. Pine 30 N71W 20 Fir 6 S61W 22

A-7 (N.W. Corner Sec. 19)
Aug. 3, 1845 John Burt, D.S. set post corner.
Tamarack 5 N24W 66 do 5 N65W 93

Sept.23/50 Algernon Merryweather, D.S. corner 18&19 West Boundary Tamarack 7 N60E 1.23 do 6 S43E 1.11

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

- A-6 No evidence of the original corner remains reestablished the corner by single proportionate measurement between corners A-5 & A-7.
- A-7 Found iron pipe set by Carl Christensen from original bearing tree "Tamarack 7" N60E 123 links" as noted in County Surveyors Book.
- C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

 A-6 Schoolcraft County monument stamped to identify

 4" Beech N24°W 7.75'

 12" Hemlock EAST 13.98'

 5" Maple S40°W 4.76'

 Post WEST 1.5'

 A-7 2" iron pipe w/2 1/2" brass cap stamped" C.C "

21274

16" Tamarack N86E 95.3' 12" Tamarack N32E 163.4' 12" Tamarack N9W 135.0.

Thomas P.O'Brien

__ Date __

PAGE: 397

March 10, 1995

Surveyor's	Michigan	License	No.
------------	----------	---------	-----

Signed by

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975