

LAND CORNER RECORDATION CERTIFICATE
FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY _____	T. <u>43</u> ^{N.} 44 R. <u>15</u> ^{W.} E.	<u>K-6, G-5</u>
2. PROPERTY CONTROLLING IN SECTION _____	T. _____ ^{N.} S. R. _____ ^{E.} W.	_____
3. MISCELLANEOUS PROPERTY IN SECTION _____	T. _____ ^{N.} S. R. _____ ^{E.} W.	_____
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Frank J. Bray do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above (identified with circles on index code diagram - over) were, in a field survey on November 1 & 2 1972 established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____ 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:
Woodposts:

G-5 W. Pine 10 820° W 6 links
 W. Pine 28 $N70^{\circ}$ E 37 links

K-6 $\frac{1}{4}$ post Tamarack 8
 Corner Tree
 Spruce 7 $S40^{\circ}$ W 25 links

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

K-6 This corner was placed midway and on a line between section corners to the north and to the south.

G-5 This corner was re-established by double proportioned measurement between section corners 1 mile to the north, east and west and 2 miles to the south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
All 1" iron pipe with $\frac{1}{4}$ " aluminum cap.

K-6	7" J. Pine ($\frac{1}{8}$ S) (NBT)	$N07^{\circ}$ E	Magnetic	15.8'
	16" R. Pine ($\frac{1}{8}$ S) (NBT)	$S12^{\circ}$ W	Magnetic	67.0'
G-5	12" J. Pine ($\frac{1}{8}$ S9) (NBT)	$N01^{\circ}$ W	Magnetic	11.0'
	10" J. Pine (S15) (NBT)	$S80^{\circ}$ E	Magnetic	17.3'

SIGNED BY _____ DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____ (SEAL)

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

APPROVED AND SIGNED BY Frank J. Bray DATE 2/9/73
MICHIGAN REGISTERED LAND SURVEYOR (SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. 13575