

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T _____ R _____ T _____ R _____ T _____ R _____	_____
2. Property Controlling in Section	S 16 T 43N R 15W S 16 T 43N R 15W S _____ T _____ R _____	8 11
3. Miscellaneous Property in Sec.	S _____ T _____ R _____ S _____ T _____ R _____	_____
4. Lot No. _____, Recorded Plat _____		
5. Private Claims _____		

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6			5		4		3		2		1	
3													
4	7			8		9		10		11		12	
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 8 02/16/2012
11 02/16/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 16) West 1/16 corner, Section 16. Not previously monumented.

(11-Sec. 16) Southwest 1/16 corner. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 16) Established the position for the corner midway and on a straight line between Quarter
corner 1321.39' west and the intersection of 1/4 lines of Sec. 16 1321.39' east.

(11-Sec. 16) Established the position for the corner at the intersection of straight lines connecting
opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
20" R.Pine N39E 36.45' mrkd "W1/16 BT"
8" R.Pine N83E 25.2' do
12" R.Pine S48E 36.0' do
6" R.Pine S82W 20.6' do
Set sq'd pine post adjacent.
Bearings are magnetic.

(11) Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
4" R.Pine N66W 13.8' mrkd "SW1/16 BT"
10" R.Pine S45E 39.9' do
12" R.Pine N81E 5.8' do
7" W.Pine N27E 19.2' do
Set sq'd pine post adjacent.
Bearings are magnetic.

Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 12/06/2012

For the Michigan Department of Natural Resources, Forest Resources Division

