

**LAND CORNER RECORDATION CERTIFICATE**  
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

Schoolcraft

(County)

Located in:

Corner Code #

1. Public Land Survey

T 43N R 15W 19

T      R     

T      R     

T      R     

2. Property Controlling  
in Section

S      T      R     

S      T      R     

3. Miscellaneous

S      T      R     

Property in Sec.

S      T      R     

Register of Deeds Stamp & File Number

4. Lot No.         , Recorded Plat         

5. Private Claims         

Dec 15 1998

I, Stephan J. Szyszkoski, in a field survey on         , 19     do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2		6		5		4		3		2		1	
3													
4		7		8		9		10		11		12	
5													
6		18		17		16		15		14		13	
7													
8		19		20		21		22		23		24	
9													
10		30		29		28		27		26		25	
11													
12		31		32		33		34		35		36	
13													

A. Description of original monument and accessories and/or subsequent restoration:

(19) Corner common to Sections 22-23-26-27. Reestablished by double proportionate measurement to the original record in 1972 by F.J. Bray, RLS. 1" pipe with 4" aluminum cap. 11" W.Pine N56W 19.6', 10" W.Pine N22E 38.5'.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(19) Recovered the 1972 monument as described, in good condition, and at record bearing and distance from the 1972 accessories. The W.Pine NW is a 6 ft. high dead snag. The W.Pine NE is in good condition. Left the monument in place and made new witnesses as described below.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(19) 1" pipe with 4" aluminum cap.

Blazed, scribed, and set measuring nails

in the following:

5" W. Pine N88E 11.95' "S23 N81"


5" W. Pine N05W 28.4' "S22 N81"

5" W. Pine S36E 29.5' "S26 N81"

The 1972 witness:

18" W. Pine N25E 39.2' "S23"

Bearings are magnetic. Dist. are to nails with tags.



Signed by

Stephan J. Szyszkoski

Date

3/21/00

Surveyor's Michigan License No.

33986

For the Michigan Department of Natural Resources - Forest Management Division