

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft

(County)

Located In:

Corner Code #

1. Public Land Survey

T R
T R
T R

2. Property Controlling
in Section

S 25 T 43N R 16W
S T R
S T R
S T R
S T R

12

3. Miscellaneous
Property in Sec.

S T R
S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims

Register of Deeds Stamp & File Number

	A	B	C	D	E	F	G	H	I	J	K	L	M
1													
2	6		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

I, Stephan J. Szyszkoski, in a field survey on 03/13/2012 do hereby state
that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2
above were in conformance with regulations and rules therefore as required in the current manual of survey
instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of
a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with
the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established,
re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded
on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(12-Sec. 25) South 1/16 corner Section 25. Not previously monumented.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(12-Sec. 25) Established the position for the corner midway and on a straight line between Quarter
corner L11 1323.94' south and the intersection of Quarter lines of Section 25 1323.94' north.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(120 Set 1"IDx36" I.pipe with 4" alum. MDNR cap.
Set measuring nail with MDNR tag in the side of:
5" J.Pine N33W 57.61' mrkd "S1/16 BT"
15" W.Pine S55W 63.06' do
14" R.Pine S20E 113.73' do
10" Maple N65E 91.76' do
Set sq'd Pine post adjacent.
Bearings are magnetic.



Signed by Stephan J. Szyszkoski

Date 05/23/2012

Surveyor's Michigan License No. 33986

For the Michigan Department of Natural Resources, Forest Resources Division