

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T____ R____	_____
	T____ R____	_____
	T____ R____	_____
	S____ T____ R____	_____
2. Property Controlling in Section	S 26 T 43N R 16W	8
	S 26 T 43N R 16W	16
3. Miscellaneous Property in Sec.	S____ T____ R____	_____
	S____ T____ R____	_____

4. Lot No. _____, Recorded Plat _____
5. Private Claims

Jan 05 2006

I, Stephan J. Szyszkoski, in a field survey on _____, 20____ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(8-Sec. 26) West 1/16 corner, Section 26. Not established in the original survey.
(16-Sec. 26) East 1/16 corner between Sections 26 and 35. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(8-Sec. 26) Established the corner midway and on a straight line between Quarter corner 1340.32' west and Center of Section 1340.32' east.
(16-Sec. 26) Established the corner on the section line and midway between Quarter corner 1322.61' west and Section corner 1322.61' east.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(8) Set 1"IDx36" I.pipe with 4" alum.	(16) Set 1"IDx36" I.pipe with 4" alum.
MDNR cap. Set measuring nails in:	MDNR cap. Set measuring nails in:
15" Maple N42W 5.9' mrkd "W1/16 BT"	25" W.Pine N63W 37.75' mrkd "E1/16 BT"
14" Maple N78E 23.8' do	5" Spruce N02W 12.5' do
11" Maple S69E 28.3' do	8" Cedar N43W 40.75' do
15" Maple S04E 34.4' do	4" W.Birch S68W 10.3' do
Bearings are magnetic. Distances are to nail with tag.	Bearings are magnetic. Distances are to nail with tag.



Signed by Stephan J. Szyszkoski
Surveyor's Michigan License No. 33986

Date 12/6/06

For the Michigan Department of Natural Resources, Office of Land and Facilities