

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County) Located In: Corner Code #
1. Public Land Survey T R
2. Property Controlling in Section S 11 T 43N R 16W 9
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

Table with 13 rows and 13 columns (A-M). Contains numbers 1-36 and survey markers.

I, Stephan J. Szyszkoski, in a field survey on Nov. 7, 2007 do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:
(9-Sec. 11) East 1/16 corner, Section 11. Not established in the original survey.

(6-Sec. 12) Northeast 1/16 corner, Section 12. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:
(9-Sec. 11) Established the corner midway and on a straight line between Center of Section 1323.12' west and Quarter corner 1323.12' east.

(6-Sec. 12) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
(9) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
6" W.Birch N58W 15.50' mrkd "E1/16 BT"
5" Maple S63W 10.62' do
12" Maple S19E 12.18' do
7" Balsam N06W 26.17' do
Bearings are magnetic.
(6) Set 1"IDx36" I.pipe with 4" alum. MDNR cap. Set measuring nail with MDNR tag in the side of:
17" W.Pine S07E 32.34' mrkd "NE1/16 BT"
21" W.Pine S71W 36.7' do
12" W.Pine N12W 21.85' do
10" Maple S89E 17.31' do
Bearings are magnetic.



Signed by [Signature] Date 11/14/07
Surveyor's Michigan License No. 33986