

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft

(County)

Located in:

Corner Code #

1. Public Land Survey

T 46N R 14W

M6

T 46N R 14W

K7

T R

S T R

2. Property Controlling  
in Section

S T R

S T R

3. Miscellaneous  
Property in Sec.

S T R

S T R

4. Lot No. , Recorded Plat

5. Private Claims

Sep 30 2003

I, Stephan J. Szyszkoski, in a field survey on \_\_\_\_\_, 20\_\_\_\_ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(M6) Quarter corner common to Section 13 T46N-R14W and 18 T46N-R13W. 1962: Biolly D. Buckler reestablished the corner midway between Section corners. Set 1"ID I.pipe with 4" aluminum cap. 8" Jack Pine N28E 11.5 links, 9" Jack Pine S74W 42.5 links.  
(K7) Corner common to Sections 13-14-23-24. 1962: The corner was reestablished by Billy D. Buckler RLS by double proportionate measurement between corners 1.5 miles North, 2 miles South, 1 mile East, and 3 miles West. Set 1" I.pipe with 4" aluminum cap. 12" Jack Pine S40E 21.5 links, 7" Jack Pine S60W 19.5 links, 10" Jack Pine N49W 25.5 links.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(M6) Found the 1962 monument in good condition and at record bearing and distance from the 1962 witnesses, both still standing. The 1962 position for this corner is not accepted due to the reestablishment by the undersigned of corners M5 and M7, upon which the position of this corner depends. I reestablished the corner midway and on a straight line between those two corners, which are 2646.46' North and South. The 1962 position, which was subsequently destroyed, is N87W 82.21' distant. Found no evidence of the bearing trees marked in the original surveys by Carleton and Burt.

(K7) Recovered the 1962 monument in good condition at record bearing and distance from the dead remains of the Jack Pine witnesses. The 1962 position for this corner is not accepted due to the reestablishment by the undersigned of Section corner M7, upon which the position of this corner depends. I reestablished the corner position by double proportionate measurement to the original record between Quarter corner 7956.85' North, Section corner 10606.64' South, Section corner 15873.79' West, and Section corner 5291.24' East. The 1962 position, subsequently destroyed, is S78W 46.49' from the corner thus established. Found no evidence of the original 1850 bearing trees.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(M6) Set a 1"IDx36" I.pipe with 4" alum.

MDNR cap. Blazed, scribed, and set

measuring nails in:

6" Maple S42W 36.1' 1/4S NBT

10" J.Pine N89W 30.75' do

8" J.Pine N47W 59.3' do

12" R.Pine S58E 60.95' do

Placed a cedar post adjacent. Bearings

are magnetic. Distances are to nail

with tag.

(K7) Set a 1"IDx36" I.pipe with 4"

alum. MDNR cap. Blazed, scribed, and

set measuring nails in:

12" J.Pine N43W 65.0' S14 NBT

24" R.Pine S15W 116.6' S23 NBT

16" R.Pine S61E 74.9' S24 NBT

12" J.Pine N78E 73.9' S13 NBT

Placed a cedar post adjacent. Bearings

are magnetic. Distances are to nail

with tag.



Signed by

*Stephan J. Szyszkoski*

Surveyor's Michigan License No.

33986

Date

11/18/03

For the Michigan Department of Natural Resources, Office of Land and Facilities