

LAND CORNER RECORDATION CERTIFICATE  
Filing Requirement of Act 74, Mich. P.A. 1970 as Amended

For corners in

Schoolcraft (County)	Located In:	Corner Code #
1. Public Land Survey	T R	
	T R	
	T R	
	T R	
2. Property Controlling in Section	S 9 T 46N R 14W	11
	S 9 T 46N R 14W	10
3. Miscellaneous Property in Sec.	S T R	
	S T R	

Register of Deeds Stamp & File  
Number

4. Lot No. , Recorded Plat  
5. Private Claims

10 Nov 13 2006  
11 Oct 02 2006

I, Stephan J. Szyszkoski, in a field survey on \_\_\_\_\_, 20\_\_\_\_ do hereby state that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

(11-Sec. 9) Southwest 1/16 corner, Section 9. Not established in the original survey.  
(10-Sec. 9) South 1/16 corner between Sections 8 and 9. Not established in the original survey.

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

(11-Sec. 9) Established the corner at the intersection of straight lines connecting opposite 1/16 corners.  
(10-Sec. 9) Established the corner midway and on the Section line between Quarter corner 1332.97' north and Section corner 1332.97' south.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

(11) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nails in: 17" W.Pine N82W 4.42' mrkd "SW1/16 BT" 10" W.Birch clump N14W 12.15' do 6" Hemlock S87E 13.09' do 10" Spruce S14E 20.46' do Bearings are magnetic. Distances are to nail with tag.	(10) Set 1"IDx32" I.pipe with 4" alum. MDNR cap. Set measuring nails in: 5" Maple N40W 9.6' mrkd "S1/16 BT" 6" Cherry S40W 18.28' do 4" Maple S53E 17.2' do 6" Maple N65E 27.75' do Bearings are magnetic. Distances are to nail with tag.
--	---



Signed by Stephan J. Szyszkoski  
Surveyor's Michigan License No. 33986

Date 12/28/06

For the Michigan Department of Natural Resources, Office of Land and Facilities