

NOV 0 3 1998

1998 REMONUMENTATION PROGRAM

LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74. Mich. P.A. 1970

SECTION		, requirement of		310				
For corners in								
Shiawassee (County)	Located In:	Comer Code				10/27/1	1 of 2 998 03:22	
1. Public Land Survey	T <u>7N</u> R <u>4E</u> T R T R			Register of Deeds Stamp & File Number				
2. Property Controlling S in Section S S Property in Sec. S	T R			A R	C. D. F. F.	G Н I J	K i M	
4. Lot No, Recorded Pla 5. Private Claims	t			2 6	5 4			
I,John H. Rauser, P.S.	, in a field survey	on April	19 98 .	4 7	8 9	10 11	12	
do hereby certify that under require in lines 1 and 2 above were in co- current manual of survey instruction	nformance with regulations of the United State	lations and rules the es Department of the	refore as required in the Interior, Bureau of Land	6 18	17 16	15 14	13	
Management or by a decree of a Corabove were in conformance with the Court of Law; established, re-e	e rules of the Michiga	an Board of Land Sur	veyors or by a Decree of a	8 19	20 21	22 23		
expressed below: NOTE: Not more than 2 corner	rs, all in the same	town and range, n	nay be recorded	10 30 11	29 28	1 1 1 1		
on this certificate.				12 31	32 33	34 35	36	
A. Description of original M-9 Std. Sec. Cor., Secs. 29 1822 Wood post placed	5 <u>& 24, T7N-R4E, V</u> by J. Wampler, D.S	<mark>Venice Township</mark> S. Sugar 12 Beech 14	2 N53W 14 lks 4 S84E 27 lks	oration:				
1868 Survey by E. Maso Continued on back.	on measured 40.01	ch (2640.66') to L-9).					
B. Description of corner e	vidence found a	nd/or method ap	plied in restoring or	reestablis	shing corner	•		
M-9 Std. Sec. Cor., Secs. 25	5 & 24, T7N-R4E, \	Venice Township	oil 9 El E of abusical co-	-4	urka himbooni ki	42 5-4	المحادما	
Fnd no evidence of origin the following witnesses:	nai governinent act	Jessones, Fila Fili	iali 2.5 E oi priysical cei				CHECKEU	
N53VV, 29.48° C S86W, 32.62' T	enter of catch bas /C Bell box (1993)	IN (1993) R=N50W,	29.55'	Cou	nty Remon	umentatic		
N76E, 24.44' N	ail w/Carlson tag S ail w/flg in N Fce P	W Fce P/P (1996) F /P (1996) R=N70E, st (1963) R=E, 34.4'	R=N70E, 24.39' N Fce P 24.39'	_ P	eer Reviev 3 oct	v Group		
S56E, 62.74' S\ S14E, 94.41' Na	√V cor foundation ⊢ ail w/Carlson tag in	lse#3037 (1963) R= N Fce P/P	SE, 62.8'					
Continued on back.	et N& 1 #32332 in	SE FCe 14" Maple (1996 & 1986) R=S40W,	52.53' N F	ce 14" Maple		,	
C. Description of monume	nt for corner an	d accessories es	tablished to perpetu	ıate locati	ng the positi	on of the c	orner:	
M-9 Std. Sec. Cor., Secs. 25 Set a standard 20" Harris the Shiawassee County	son monument and	l placed a 4" monun		•	e at the position	approved b	y	
N53W, 29.48' Center of o West, 2.5' Cl. of state hig	ghway M-13		# 7/ Augus	CHIEN				
S86W, 32.62' T/C Bell bo			JOHN RAUS					
\$87W, 32.90' ½" Rod N78E, 23.78' Nail w/Carl	son tag SW Fce P	'P	MOFES	HONAL				
N76E, 24.44' Nail w/fig ir	N Fce P/P	-	Tal Marve		Ö			
N77E, 34.20' Iron pipe in S56E, 62.74' SW cor fou			Tal mo		1			
S14E, 94.41' Nail w/Carls	son tag in N Fce P.	/P	TO MOST	ide	•			
S40W, 53.16' Set N&T #			CONTR	100				

Signed by Surveyor's Michigan License No. 39096

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971 REVISED MAY 14, 1975 REVISED JAN., 1983 ADAPTED FOR WORD PROCESSING MARCH, 1993

A: Continued:

1876 Survey by E. Mason.

Appletree 5" S49W 142 lks

1889 Survey by A. Huggins.

Appletree 7" S50W 94'

1949 Original Plat of Lennon by O.M. Elliot. No witnesses.

1949 Don Bingham of Flint measured 2644.20' to L-9.

1950 F.A. Gould Drain Record Book 11, P. 85. M-9 is 12' W of E edge pavement; 2' E of CL

1956 Plat of Peelman Subdivision uses M-9.

1958 O.M. Elliot C.S. calls for box in pavement. No witnesses.

1963 Survey by Consumers Power Co. dwg# S-F 16602. Fnd 1½ " x 1½" wood stake in mon box, 3.0' E of CL of pavement.

East 34.3' Iron in top of conc post

SE 62.8' SW corner of Hse#3037 foundation

1971 Act 132 by D. Rowe L. 1, P. 3; fnd 1-1/4" lead pipe.

N21W 75.4' 15" Elm N54E 39.8' 4" Maple S25E 56.1' 12" Box Elder East 2.2'+ CL of Sheridan

1974 Act 132 by E.S. Brewer L. 2, P. 323; uses M-9. No witnesses.

1975 Act 74 by J. Quine fnd Iron rod in mon box. West 2.4' CL M-13

South 165', 330', & 487' PK's on section line

North 357', SW corner Section 19, T7N-R5E Iron in mon box. 1976 Act 132 by Rowe Engineering Inc., Job # F-5177-76; fnd 1-1/4" lead pipe.

N54E 39.8' 4" Maple

N13W 75.4' 15" Elm

S25E 56.1' 12" Box Elder

West 2.2' CL Sheridan Ave/M-13

1986 Act 132 by J.D. Matonich, L. 4, P. 444; set PK using CPCO witnesses.

N70E 34.30' Fnd Iron rod in top conc post

S40E 62.80' SW cor. block fnd Hse#3037

N70E 24.39' Set nail w/fig in N Fce P/P

S40W 52.53' Set PK w/flg in N Fce 14" R. Maple

West 2.7' CL pavement M-13

1989 Act 74 by N.C. Caldwell, L. 2, P. 623; fnd PK nail in pavement per M.D.O.T. R/W plans, N 356' NW cor Section 30. 1989 Act 132 by N.C. Caldwell, L. 5, P. 294; fnd PK nail in pavement per M.D.O.T. R/W plans, N 356' NW cor. Section 30. 1992 Act 132 by M. L. VanRaemdonc, L. 6, P. 185; Set PK nail using CPCO witnesses.

N70E 34.30' Fnd Iron rod in top conc post S40E 62.80' SW cor. block fnd Hse#3037 N70E 24.39' Set nail w/flg in N Fce P/P

S40W 52.53' Set PK w/flg in N Fce 14" R. Maple

West 2.7' CL pavement M-13

1993 Act 132 by M.L. VanRaemdonc, L. 7, P. 694; fnd PK nail.

West 32.82' Top center telephone cable cabinet

N50W 29.55' Center catch basin cabinet

West 2.35' Physical CL M-13

N80E 24.40' Spike & flag N side utility pole

SURVEY &

1996 Act 132 by M.L. VanRaemdonc, L. 7, P. 010; fnd PK nail. REMONUMENTATION

N70E 34.30' Fnd Iron rod in top conc post S40E 62.80' SW cor block fnd Hse#3037

N70E 24.39' Nail w/flg in N fce P/P

S40W 52.53' PK w/flg in N fce 14" R. Maple

West 2.7' CL pavement M-13

NOV 03 1998

SECTION

B. Continued:

Measured West to L-9 2644,48'

Prior 1949 Bingham 2644.20'

1876 L. Mason 2627.79 1949 F.A. Gould 2645,10' 1963 CPCO

2644.03' 1866 E. Mason 2640.66

Upon excavation to set the Harrison monument a 1 ½" x 1 ½" wood stake was found in a monument box as per the 1963 Consumer Power survey at this position. Accepted fnd PK above found wood stake as the best available evidence of the position of the original government





Page: 2 of 2 10/27/1998 03:22P

Lb-1 Pg-275