

# SURVEY & REMONUMENTATION

NOV 10 1997

## LAND CORNER RECORDATION CERTIFICATE

Filing Requirement of Act 74, Mich. P.A. 1970

### COMMISSION

For corners in

Shiawassee  
(County)

Located In:

Fairfield Twp

Corner Code #

RECORDED

97 OCT 15 PM 12:13

REGISTER OF DEEDS

SHIawassee COUNTY, MICH

Register of Deeds Stamp & File Number, MICH

1. Public Land Survey

T 8N R 1E

D-1

2. Property Controlling  
in Section

S T R

3. Miscellaneous  
Property in Sec.

S T R

4. Lot No. , Recorded Plat

5. Private Claims

I, Wendy A. Papineau, in a field survey on June 1997

do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

D-1 Closing Township Corner, Section 5, T8N-R1E and Section 32, T9-R1E

Wood post placed by Robert Clark, Jr. D.S. Feb. 27, 1831  
S24E 40 lks (26.40') 16" Elm  
N28 1/2E 52 lks (34.32') 10" Birch  
South 58.28 ch (3846.48') Township Corner, T8 & 9N- R1W

Shiawassee County Survey by Lyman Mason, June 1876. Recorded in Book D, Pgs 118-119, S.C.D.R.  
"Stake and Stones"  
N4 55'E 215 lks (141.90') 8" Oak

Gratiot County Survey by Thomas H. Harrod, C.S., April 5-7, 1880. Recorded in Book C, Pg.41, G.C.R.  
Iron bar 1" x 32" long- stones- o.c.f. Walnut 14" 43.4 lks (28.64')  
NW 110.8' Dbl Butternut  
E & W 25' stakes  
South 58.28 chs (3846.48') to the Standard Township Corner, Sec. 1, T8N-R1W and Sec.36, T9N-R1W

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

D-1 Closing Township Corner, Section 5, T8N-R1E and Section 32, T9-R1E

Found 3/4" pipe, with occupation East and 0.66' East of the Michigan Meridian. This position fits well with the G.L.O. closing distance and the Gratiot County record (record 58.28 ch = 3846.48' meas. 3847.45')

Calculated a true position for the closing corner on the Michigan Meridian

During excavation for placement of Harrison monument, found record stone on the Michigan Meridian. Removed stone and found no more evidence. The position of the stone is accepted as a careful and faithful perpetuation of the position of the original corner.

Approved by the Shiawassee County Remonumentation Peer Review Group 9 OCT 1997

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

D-1 Closing Township Corner, Section 5, T8N-R1E and Section 32, T9-R1E

Placed a standard Harrison monument 0.6' below gravel surface  
West 13.25' Set 1/2" rod in forward slope of ditch bank  
N20E 113.55' Set N&T #39096 in Wly fc of 24" Walnut  
N45E 58.12' Set N&T #39096 in SE fc Tele. Pole  
S86E 32.30' North side, center of 6" steel post  
S88E 50.40' Set N&T #39096 in S. fc P/P  
South 3847.45' Fnd Clinton Co. Remon. cor. @ the Standard Township Corner,  
Sec. 1, T8N-R1W and Sec.36, T9N-R1W



Signed by Wendy A. Papineau

Date 10-09-97

Surveyor's Michigan License No. 41919

LIBER 1R PG 188

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28, 1971  
REVISED MAY 14, 1975  
REVISED JAN., 1983  
ADAPTED FOR WORD PROCESSING MARCH, 1993

A PORTION OF

THE

# MICHIGAN MERIDIAN

A

RETRACEMENT AND REMONUMENTATION PROJECT  
FOR

CLINTON AND SHAWASSEE COUNTIES, MICHIGAN

MARCH - SEPTEMBER 1997

BY  
**ROWE ENGINEERING, INC.**  
112 E MCARTHUR STREET  
CORUNNA, MI 48837

BEARINGS ARE BASED ON A  
PREVIOUS REMONUMENTATION  
PROJECT JANUARY THROUGH  
MAY 1998 BY ROWE ENGINEERING, INC.  
JOB NO. S-4830 AND ALSO A SOLAR  
OBSERVATION AT THE NORTH END OF  
THE 1997 REMONUMENTATION PROJECT



SHEET 2 OF 2 SHEETS

LIBER 1R PG 189

CLINTON COUNTY

CLINTON COUNTY

GRATIOT COUNTY

DUPLAIN TOWNSHIP  
(T8N-R1W)

ELBA TOWNSHIP  
(T8N-R1W)

SAGINAW COUNTY

COUNTY

SHIAWASSEE

FAIRFIELD TOWNSHIP  
(T8N-R1E)

CHAPIN TOWNSHIP  
(T8N-R1E)

SURVEY &  
REMONUMENTATION

NOV 10 1997

COMMISSION

