

# SURVEY & REMONUMENTATION

FILED

JAN 14 1998

## VAN BUREN COUNTY REMONUMENTATION LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

DEC 16 12 00 PM '97

For corners in **SECTION** Located in: Corner ID #  
VAN BUREN COUNTY COLUMBIA TWP. W 1/4 SEC 7 T1S, R16W

*Mark A. Smith*  
VAN BUREN CO.  
REGISTERED FOR THE

1. Public Land Survey T 1S R 16W A-4  
T      R       
T      R       
T      R
2. Property Controlling S      T      R       
in Section S      T      R
3. Miscellaneous S      T      R       
Property in Sec. S      T      R
4. Lot No.      Recorded Plat
5. Private Claims

*Liber 5 PAGE 56*

Register of Deeds Stamp & File Number

I, Alan Bartlett in a field survey on December 8 1997 hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	8		5		4		3		2		1		
3													
4	7		8		9		10		11		12		
5													
6	18		17		16		15		14		13		
7													
8	19		20		21		22		23		24		
9													
10	30		29		28		27		26		25		
11													
12	31		32		33		34		35		36		
13													

A. Description of original monument and accessories and/or subsequent restoration:  
NOT SET BY GOV'T. SURVEY

10/1901 GOSS NOTES PAGE 7  
SET OAK STAKE MIDWAY BETWEEN SECTION COR. (NOTES)

10/1901 W.H. GOSS BOOK 1 PAGE 88  
LOCATED THIS CORNER MIDWAY BETWEEN "1" AND "4" ON TOWN LINE 35 1/2 LINKS (23.43') SOUTH FROM GENEVA QUARTER POST.  
SET OAK STAKE 39.99 1/4 NORTH AND SOUTH (2639.67')

Ratified by Peer Group in  
accordance with P.A. 345 of 1990  
Van Buren County Surveyor

Date D. R. A. 12/16/97

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

USING HALFWAY DISTANCE BETWEEN A-3 AND A-5 (NW AND SW CORNER OF SECTION 7) AS APPROVED BY VAN BUREN COUNTY PEER GROUP REESTABLISHED W 1/4 CORNER ON TOWNSHIP LINE BETWEEN M-4 AND M-5 OF GENEVA TWP. THIS GOVERNMENT MONUMENT WAS RESTORED WITH APPROVAL OF THE VAN BUREN COUNTY REMONUMENTATION PEER GROUP OF SURVEYORS ON NOVEMBER 19 1997.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

SET 2 1/2" HARRISON MONUMENT AND MONUMENT BOX 2.5' EAST OF CENTER LINE OF COUNTY ROAD 681 AND ON CENTER LINE OF DITCH TO THE EAST.

WITNESSES	
N75°E 92.88'	NAIL AND FLASHER ON N. SIDE OF 8" LOCUST
S45°E 52.52'	FOUND NAIL ON NORTH SIDE OF POWER POLE
NORTH 23.45'	E 1/4 CORNER OF SECTION 12 (HARRISON MONUMENT IN MONUMENT BOX)
N55°W 79.29'	TOP CENTER LINE OF STEEL FENCE POST

THIS POSITION NOT ESTABLISHED BY ORIGINAL GOVERNMENT SURVEYORS. THIS MONUMENT IS ACCEPTED AS THE BEST AVAILABLE EVIDENCE OF THE POSITION OF THIS CORNER.

Signed by Alan K. Bartlett Date 12/15/97  
Surveyor's Michigan License No. 35988

