

RECORDED

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A. 1970

DEC 17 9 26 AM '98

W 1/4 POST SEC 15 T2S R15 W ARLINGTON TWP

Mark A. Smith
VAN BUREN CO.
REGISTER OF DEEDS

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____ T. <u>2</u> N. S., R. <u>15</u> W.		<u>G-6</u>
2. PROPERTY CONTROLLING IN SECTION_____, T. _____ N. S., R. _____ E. W.		
3. MISCELLANEOUS PROPERTY IN SECTION_____, T. _____ N. S., R. _____ E. W.		
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

LIBER 5 PAGE 174

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, CHARLES D. LOSSIE, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on 12/11, 1998 established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

SEE BACK SHEET

SURVEY &
REMONUMENTATION

JAN 11 1999

SECTION

Retified by Peer Group in
accordance with P.A. 345 of 1990
Van Buren County Surveyor

Date D.R.A. 12-17-98

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

FOUND 1/2" PIPE IN MONUMENT BOX, SET OVER 3/4" IRON AND BRICK.
FOUND 1/2" PIPE SET OVER 3/4" IRON AND BRICK WAS ACCEPTED AS BEST
AVAILABLE EVIDENCE OF THE POSITION OF THE ORIGINAL CORNER AT A
PEER GROUP MEETING HELD ON 8/26/98.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

TIED OFF 1/2" PIPE. SET HARRISON MARKER AND MONUMENT BOX.
POWER POLE S. 30° E. 128.39' TO PK AND WASHER
NW CORNER OF BRICK BLD. S. 70° W. 118.35'
SW CORNER OF ARLINGTON TOWNSHIP HALL N. 60° W. 101.52'.
NE CORNER OF ARLINGTON TOWNSHIP HALL N. 30° W. 121.36'.

SIGNED BY Charles D. Lossie DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. 44291

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____

CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____

MICHIGAN REGISTERED LAND SURVEYOR

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

LIBER 5 PAGE 175

**WEST QUARTER POST OF SECTION 15
TOWN 2 SOUTH, RANGE 15 WEST ARLINGTON TOWNSHIP (G-6).**

- 4/1830- GOVERNMENT - G. W. Harrison, D.S.**
Ran North between Sections 15 & 16 a distance of 40.00 chs. and set post corner.
WITNESSES: 12" Sycamore - S. 40° E. 25 lks. (16.50').
8" Sycamore - N.28° W. 25 lks. (16.5').
- 8/1918 - May Be Goss, C.S. ??**
Section 15. Red Book & Goss notes. Stake, Stones and P. Point.
- 1930± - T. A. Smith, C.S.**
Red book. 3/4" solid iron rod.
WITNESSES: 30" Walnut - N. 52° 15' W. 50.85' to spike.
26" Walnut - N. 48° 30' E. 47.55' to spike.
26" Maple - S. 44° 30' W. 52.8' to spike.
- 4/15/1971 - W. Q. Smith, C.S. (D. a. Middleton, R.L.S.).**
Section 16. Recorded Survey (Liber 1 - Page 10). Found pipe.
WITNESSES: 30" Walnut - N. 52° 15' W. 50.85' to center line.
Street Sign - Southeast 42.35' to center line.
Center line - Center line of intersection.
- 5/26/1971 - D. A. Middleton, R.L.S.**
Recordation Certificate (Liber 1 - page 20).
Same as above.
Distance South is 2636.46'.
- 6/4/1971 - J. C. Hunt, R.L.S.**
Section 15. Recorded Survey (Liber 1 - Page 110).
WITNESSES: Southeast corner of Township Hall N. 45° W. 81.0'.
Red Brick Bld. - Southeast corner - S 45° W. 87.8'.
Street Sign - S 45° E. 42.3'.
- 5/11/1972 - W. Q. Smith, C.S.**
Section 16. Recorded Survey (Liber 2 - Page 59).
Shows quarter post (found pipe).
Witnesses same as W.Q. Smith on 4/15/1971.
Distance West is 2681.72' to Center Quarter Post at computed intersection.
Distance South is 2635.67'.
6/22/1972 - Recorded Survey (Liber 3 - Page 175).
Same as W.Q. Smith on 4/15/1971.
6/22/1972 - Recorded Survey (Liber 2 - Page 101).
Same as W.Q. Smith on 4/15/1971.
- 8/10/1972 - A. W. Howard, R.L.S.**
Section 15. Recorded Survey (Liber 2 - Page 255).
1" iron pipe & witnesses same as J.C. Hunt on 6/4/1971.

**SURVEY &
REMONUMENTATION**

JAN 11 1999

SECTION