

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

WAYNE

(County)

Located In: PLYMOUTH TWP. Corner Code #

1. Public Land Survey T 1 S R 8 E G-12
T R
T R
T R
2. Property controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. , Recorded Plot
5. Private Claims

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 12-13-1996
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE
Register of Deeds Stamp & File Number

96327769

I, CHRISTOPHER S. LAMUS, in a field survey on DECEMBER 16, 19 96, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate

A. Description of original monument and accessories and/or subsequent restoration: \$ 4.00 REMONUMENTATION
DRIG. GOVERNMENT NOTES 1815
BY JOSEPH WAMPLER - SET POST
24' WHITE OAK S.56°W. 14 LINKS (1)
26' WHITE OAK S.75°E. 12 LINKS (2)

\$ 7.00 DEED
27 DEC 96 11:49 A.M. RECEI A
RECORDED
FOREST E. YOUNGBLOOD, REGISTER EDS
WAYNE COUNTY, MI

NO G.L.D. WITNESSES REMAIN

B. Description of corner evidence and/or method applied in restoring or reestablishing corner:
WAYNE CO. BUREAU OF TAXATION (1930'S) PUBLIC ACT 74 L.C.R.C. L.18313, P.738
IRON IRON IN MON. BOX.
N.E. 53.61' TEL. POLE (3) GONE S.E. 63.11' TELE. POLE (9) GONE
S.E. 41.01' 18' WALNUT (4) GONE S.W. 69.46' 21' ELM (10) GONE
S.W. 33.84' 15' MAPLE (5) GONE
S.W. 57.97' 15' MAPLE (6) GONE
N.W. 64.07' FENCE POST (7) GONE
PUBLIC ACT 74 L.C.R.C. L.18086, P.438
5/8" ROD MONUMENT BOX.
N.25°E. 57.31' 5' BOX ELDER (8) GONE
S.30°E. 63.11' TELE. POLE (9) GONE
S.45°W. 69.46' 21' ELM (10) GONE
N.40°W. 59.28' 12' ELM (11) GONE
PUBLIC ACT 74 L.C.R.C. L.20423, P.252
FOUND 3/4" BOAT SPIKE IN MON. BOX
N.43°W. 59.19' 14' ELM (11) GONE
S.40°W. 69.21' NAIL IN N.W. FACE OF 12" ELM (12) GONE
N.31°E. 64.05' NAIL IN SE SIDE OF DE POLE (13) FOUND
S.64°E. 92.58' TOP PLUG OF F.HYDRANT (14) FOUND
FOUND 5/8" ROD IN MONUMENT BOX.

DISTANCE TO G-11 2653.92' (M) RECORDED AS 2654.17' BY WAYNE COUNTY BUREAU OF TAXATION.
DISTANCE TO G-13 2647.21' (M) RECORDED AS 2650.00' BY WAYNE COUNTY BUREAU OF TAXATION.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:
G-12
5/8" ROD IN MONUMENT BOX.
SET SURVEYOR'S CAP # 41914, UNABLE TO SET W.C. REMON CAP DUE TO SIZE OF IRON ROD.
MONUMENT IS LOCATED AT THE INTERSECTION OF CANTON CENTER RD. AND ANN ARBOR RD.
IN AN ASPHALT PAVED SURFACE WITHIN THE ROAD RIGHT-OF-WAY.
N.35°E. 64.20' NAIL IN SE SIDE OF DE POLE (13) FOUND
S.65°E. 92.33' TOP PLUG OF F.HYDRANT (14) FOUND
S.30°W. 84.40' N.E. CORNER OF HSE. #45411
N.20°W. 62.60' SET W.C. REMON TAG IN E. SIDE OF 10' TWIN MAPLE
N.60°E. 87.83' SET W.C. REMON TAG IN E. SIDE OF 13' MAPLE



THE SELECTED LOCATION IS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Christopher S. Lamus
Surveyor's Michigan License No. 41914

Date 12/26/96

4R
70
D.J.