

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

\$ 7.00 DEED
RECORDATION
RECEIVED
FOREST E. YOUNGBLOOD, REGISTER
WAYNE COUNTY, MI

For corners in

WAYNE

(County)

Located In:
GREENFIELD TWP

OTHER
Corner Code #

1. Public Land Survey

T 1S R 12E

015

2. Property Controlling
in Section

S T R
S T R

3. Miscellaneous
Property in Sec.

S T R
S T R

4. Lot No. , Recorded Plat

5. Private Claims T.T.A.T. - S.E. COR. 1/4 SEC.18, INTERSECTION OF CARPENTER & DEQUINDRE

LIBER 29356 PAGE 112
Compliance with
ACT 345, P.A. 1990

APPROVED ON: DEC. 6, 1996
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE
Register of Deeds Stamp & File Number

I, MARTIN C. DUNN, in a field survey on OCTOBER 10, 1996, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

10	9	8	7	6	5	4	3	2	1
11	12	13	14	15	16	17	18	19	20
30	29	28	27	26	25	24	23	22	21
31	32	33	34	35	36	37	38	39	40
50	49	48	47	46	45	44	43	42	41
51	52	53	54	55	56	57	58	59	60

TEN THOUSAND ACRE TRACTS
CITY OF DETROIT

A. Description of original monument and accessories and/or subsequent restoration:

TEN THOUSAND ACRE TRACTS SURVEYED BY JOSEPH FLETCHER IN 1816

PLATS

L. 15 P. 31 GRACE AND ROOS ADDITION TO NORTH DETROIT
L. 27 P. 85 HUDSON AND HANNAN SUBDIVISION
L. 49 P. 32 DEQUINDRE INDUSTRIAL SUBDIVISION

MARCH 26, 1891
DECEMBER 1, 1911
MAY 16, 1924



B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND RAILROAD SPIKE AT THE CORNER OF CARPENTER AND DEQUINDRE (ASPHALT).

VERIFIED CORNER LOCATION USING FOUND IRONS, BACK OF CURB SPLITS, AND BACK OF WALK SPLITS WITH REFERENCE TO THE ABOVE LISTED PLATS, VERIFIED DISTANCE TO ADJACENT 1/4 SECTION CORNER.

FIELD MEASUREMENTS AND RECORDED DISTANCES

S.E. 1/4 COR. SEC. 18 T.T.A.T. TO S.E. 1/4 COR. SEC. 19 T.T.A.T. 2655.44' (MEASURE) 40 CHAINS (FLETCHER) 2655.80' (L. 15 P. 31)

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

PLACED BRASS WAYNE COUNTY REMONUMENTATION WASHER AND PLASTIC CAP #30081 ON 1/2" x 18" IRON REBAR WITHIN A NEW MONUMENT BOX.

WITNESSES

N.7°E. 21.23' SET PK NAIL WITH WAYNE COUNTY REMONUMENTATION TAG IN ASPHALT WALK
S.18°E. 34.83' SET PK NAIL WITH WAYNE COUNTY REMONUMENTATION TAG IN ASPHALT WALK
S.34°W. 43.64' SET PK NAIL WITH WAYNE COUNTY REMONUMENTATION TAG IN SOUTHEAST FACE OF UTILITY POLE
S.73°W. 35.08' SET PK NAIL WITH WAYNE COUNTY REMONUMENTATION TAG IN NORTH FACE OF GUARD RAIL

THE SELECTED LOCATION FOR THIS PROPERTY CONTROLLING MONUMENT IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

Signed by Martin C. Dunn Date 12-23-96

Surveyor's Michigan License No. 30081