

APR 05 1996

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in COMMISSION

WAYNE

(County)

Located in:
HARPER WOODS

Corner Code #

025

1. Public Land Survey T 1S R 13E
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R

Compliance with
ACT 345, P.A. 1990

APPROVED ON: DEC 5 1995
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat
5. Private Claims POINT COMMON TO PC's #123 & #404 @ CENTERLINE OF KELLY ROAD

I, MARTIN C. DUNN, in a field survey on OCTOBER 29, 19 95, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

GLO POST - NO EVIDENCE OF ORIGINAL CORNER FOUND

GLO ORIGINAL SURVEY PERFORMED BY AARON GREELY 1809-1811
RESURVEYED BY JOHN MULLET 11-23-1823 TO 11-6-1824

PLATS

L.50P.77 DALBY'S EAST POINTE SUB'n AUGUST 25, 1924
L.54P.11 PARK DRIVE SUB'n No.4 APRIL 30, 1925
L.68P.75-6 JOSEPH HOLTZMAN SUBDIVISION AUGUST 14, 1941



95263100

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

NO EVIDENCE OF CORNER FOUND

RE-ESTABLISHED NORTH LINE OF KELLY ROAD USING FOUND IRONS
OFFSET LINE RECORD DISTANCE (60 FEET) TO ESTABLISH NORTH LINE OF PRIVATE CLAIM #123 & #404
CAME SOUTHWEST RECORD DISTANCE (579.35 FEET) ALONG NORTH LINE OF PRIVATE CLAIM #123 FROM FD. IRON IN MON BOX
VERIFIED LOCATION WITH STONE CURB SPLITS AND SIDEWALK SPLITS.

PLACED WAYNE COUNTY REMONUMENTATION MARKER AND ALUMINUM CAP #30081 ON 1/2" x 18" IRON
WITHIN A MONUMENT BOX.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

T.1S., R.13E. WAYNE COUNTY REMONUMENTATION MARKER AND ALUMINUM CAP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX.

WITNESSES

AZ 60° 25.75' SET PK NAIL AND W.C.R. TAG IN SOUTH FACE OF LIGHT POLE
AZ 163° 75.32' SET PK NAIL AND W.C.R. TAG IN EAST FACE OF LIGHT POLE
AZ 198° 70.08' SET PK NAIL AND W.C.R. TAG IN EAST FACE OF LIGHT POLE
AZ 309° 26.99' SET PK NAIL AND W.C.R. TAG IN TOP OF CONC. CURB

THE SELECTED LOCATION IS FOR THIS PROPERTY CONTROLLING MONUMENT IS ACCEPTED AS A CAREFUL AND FAITHFUL DETERMINATION OF THE POSITION INDICATED.

Signed by Martin C. Dunn

Date DECEMBER 5, 1995

Surveyor's Michigan License No. 30081

95 DEC -8 PM 2:12
FOREST E. YOUNGBLOOD
REGISTER OF DEEDS

4
7D
NR.