APR 0 5 1996

For corners in

	LAND CORNER RECORDATION CERTIFICATE
COMMISSION	Filing Requirement of Act 74, Mich. P.A. 1970

WAYNE	Located In:	Corner Code #		
(County)	CITY OF DETROIT		•	
1. Public Land Survey	T 2S R 12E	011_	Compliance with ACT 345, P.A. 1990	
	T R		APPROVED ON: DEC 5 1995 MCX	2
	T R		WAYNE COUNTY REMONUMENTATION	_
2. Property Controlling	S T R		PEER GROUP COMMITTEE	
in Section	S TR			
3. Miscellaneous	S R		Register of Deeds Stamp & File Number	
Property in Sec.	S IH		· · · · · · · · · · · · · · · · · · ·	
4. Lot No, Rec	corded Plat		ABCDEFGHIJK	L M
5. Private Claims PO	INT COMMON TO P.C.'S #724 & #68	8 AT CENTERLINE OF FRUED .	AVE. 2 0 5 4 3 2	•
			3	
			4 7 8 9 10 11	-12
1 MARTIN C. DUNN	, in a field survey on	OCTOBER 22 19 95	5	
	quirements of P.A. 74, Michigan P./		8 18 17 16 15 14	-13-
	ve were in conformance with reg		7	+
	nual of survey instructions of the langement or by a decree of a C		8 - 19 - 20 - 21 - 22 - 23 -	- 24 —
corner points mentioned in line	s 3, 4 and 5 above were in confo	rmance with the rules of the	3	
	veyors or by a Decree of a Cou re-monumented, recovered, found		10 30 29 28 27 28	- 26
re-established, mondification,	in the state of th	as expressed below.	" + + + + + + + + + + + + + + + + + + +	
NOTE: Not more than 4	corners, all in the same tow	n and range, may be	12 31 32 33 33 36 36	-36 —
recorded on this	certificate.			
			•	٩
A. Description of original n	nonument and accessories and/o	or subsequent restoration:	· \	<u>ر</u>
NO CORNER SET IN	N ORIGINAL GOVERNMENT SURV	EY .	\	2
	· ·		•	Č
	-		******	(
<u>PLATS</u>		·	Collision of the Collis	(
L. 58 P. 62 L. 59 P. 13	~ KEAN'S FREUD AVENUE SUBI KEAN'S FREUD AVENUE SUBI		JANUARY 12, 1926 HILL OF MICHGAN	.
2,021.10	^- ,		MARTIN C.	3
	•••	•	* DUNN	3
			PROFESSIONAL SURVEYOR	
B. Description of corner e	vidence found and/or method ar	pplied in restoring or reestabl	ishing corner: SURVEYOR Constitution No. 30081	į
			ishing corner: SURVEYOR SURVEYOR SOURCE SOUR	SUSSECTION
FOUND PK NAIL			OFESSION ALLIST	3 1
VERIFIED LOCATI	ION OF CORNER BY FOUND MON	U <mark>MENTS WITH REFERENCE T</mark> C	THE ABOVE LISTED PLATS. THE ABOVE LISTED PLATS.	. ~
				S.
				E C
		v · · · · ·	· · · · · · · · · · · · · · · · · · ·	· 4
				œ
PLACED WAYNE (COUNTY REMONUMENTATION M	ARKER AND ALUMINUM CAP#	/30081 ON 1/2" x 18" IRON	3
WITHIN A MONUN	MENT BOX.		্লুর্কু	,
			· · · · · · · · · · · · · · · · · · ·	∼
		المحجول ممجر بمحجوب حم ادخاطا	no the position of the corner:	
C. Description of monumen	t for corner and accessories est	abiisned to perpetuate iocati	or and provide the second	
	i.	· •		•
T.2S., R.12E. WAY!	i.	· •	AP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX	•
T.2S., R.12E. WAY! WITNESSES	NE COUNTY REMONUMENTATION	N MARKER AND ALUMINUM C		•
T.2S., R.12E. WAY! <u>WITNESSES</u> AZ. 50° 86.6	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH	N MARKER AND ALUMINUM C. FACE OF UTILITY POLE		
T.2S., R.12E. WAY! <u>WITNESSES</u> AZ. 50° 86.4 AZ. 108° 54.3	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH N 10' SET PK WITH TAG IN WEST FA	N MARKER AND ALUMINUM C FACE OF UTILITY POLE ACE OF 12" SYCAMORE		5
T.2S., R.12E. WAY! <u>WITNESSES</u> AZ. 50° 86.6 AZ. 108° 54.1 AZ. 197° 45.4	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH I 10' SET PK WITH TAG IN WEST FA 40' SET PK WITH TAG IN EAST FA	N MARKER AND ALUMINUM C FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE		5
T.2S., R.12E. WAY! <u>WITNESSES</u> AZ. 50° 86.4 AZ. 108° 54.3	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH I 10' SET PK WITH TAG IN WEST FA 40' SET PK WITH TAG IN EAST FA	N MARKER AND ALUMINUM C FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE		5 2.
T.2S., R.12E. WAY! WITNESSES AZ. 50° 86.4 AZ. 106° 54.3 AZ. 197° 45.4 AZ. 353° 33.4	NE COUNTY REMONUMENTATION 60° SET PK WITH TAG IN SOUTH I 10° SET PK WITH TAG IN WEST FA 40° SET PK WITH TAG IN EAST FA 61° SET PK WITH TAG IN EAST FA	N MARKER AND ALUMINUM C. FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE ACE OF UTILITY POLE	AP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX	3
T.2S., R.12E. WAY! WITNESSES AZ. 50° 86.6 AZ. 108° 54.1 AZ. 197° 45.4 AZ. 353° 33.6 THE SELECTED LC	NE COUNTY REMONUMENTATION 60° SET PK WITH TAG IN SOUTH I 10° SET PK WITH TAG IN WEST FA 40° SET PK WITH TAG IN EAST FA 61° SET PK WITH TAG IN EAST FA	N MARKER AND ALUMINUM C. FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE ACE OF UTILITY POLE		5
T.2S., R.12E. WAY! <u>WITNESSES</u> AZ. 50° 86.6 AZ. 108° 54.1 AZ. 197° 45.4 AZ. 353° 33.6 THE SELECTED LC	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH IT 10' SET PK WITH TAG IN WEST FA 40' SET PK WITH TAG IN EAST FA 61' SET PK WITH TAG IN EAST FA DOCATION IS FOR THIS PROPERTY	N MARKER AND ALUMINUM C. FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE ACE OF UTILITY POLE	AP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX	5 2.
T.2S., R.12E. WAYI WITNESSES AZ. 50° 86.0 AZ. 106° 54.3 AZ. 197° 45.0 AZ. 353° 33.0 THE SELECTED LC DETERMINATION	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH IT 10' SET PK WITH TAG IN WEST FA 40' SET PK WITH TAG IN EAST FA 61' SET PK WITH TAG IN EAST FA DOCATION IS FOR THIS PROPERTY	N MARKER AND ALUMINUM C. FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE ACE OF UTILITY POLE CONTROLLING MONUMENT I	AP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX	2.
T.2S., R.12E. WAY! <u>WITNESSES</u> AZ. 50° 86.6 AZ. 108° 54.1 AZ. 197° 45.4 AZ. 353° 33.6 THE SELECTED LC	NE COUNTY REMONUMENTATION 60' SET PK WITH TAG IN SOUTH IT 10' SET PK WITH TAG IN WEST FA 40' SET PK WITH TAG IN EAST FA 61' SET PK WITH TAG IN EAST FA CCATION IS FOR THIS PROPERTY OF THE POSITION INDICATED.	N MARKER AND ALUMINUM C. FACE OF UTILITY POLE ACE OF 12" SYCAMORE ACE OF 12" SYCAMORE ACE OF UTILITY POLE	AP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX 7 J 7/A S ACCEPTED AS A CAREFUL AND FAITHFUL	Σ.