APR 0 5 1996

COMMISSION

## LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

		٠	- P-	R.Y	d	3 7		•
For	cornere	in						

3. Miscellaneous

Property in Sec.

WAYNE Located In: Corner Code # CITY OF DETROIT 012 1. Public Land Survey 28 R 12E Т R R T 2. Property Controlling R in Section S Т R

T

Compliance with ACT 345, P.A. 1990

LIBER 28452 PAGE

DEC

APPROVED ON: WAYNE COUNTY REMONUMENTATION PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

, Recorded Plat

POINT COMMON TO PC#100 & #679 @ CENTERLINE OF JEFFERSON AVE. 5. Private Claims

R

OCTOBER 22, 19 95 in a field survey on do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and /or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

Description of original monument and accessories and/or subsequent restoration:

NO CORNER SET IN ORIGINAL GOVERNMENT SURVEY

а 10 11 12

**PLATS** 

L. 4 P. 98 L. 21 P. 39 L. 21 P. 99

COMMISSIONER'S SUBDIVISION OF PART OF THE VAN DYKE ESTATES & FARM CHAS BEWICK'S SUB. OF THE SUBDIVISION OF LOTS 82, 83, & 84, VAN DYKE FARM PARKER'S RE-SUB OF LOTS 77, 78, 79, 80, & 81, VAN DYKE FARM

JULY 6, 1878 **FEBRUARY 28, 1899 OCTOBER 16, 1900** 

Description of corner evidence found and/or method applied in restoring or reestablishing corner:

NO EVIDENCE OF CORNER

ESTABLISHED CENTERLINE OF VAN DYKE AND JEFFERSON USING CURB SPLITS. VERIFIED LOCATION WITH FOUND IRONS AND PIPES ALONG WITH BLOCK SPLITS.



PLACED WAYNE COUNTY REMONUMENTATION MARKER AND ALUMINUM CAP #30081 ON 1/2" x 18" IRON WITHIN A MONUMENT BOX.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

T.2S., R.12E.

WAYNE COUNTY REMONUMENTATION MARKER AND ALUMINUM CAP #30081 ON 1/2" x 18" ROD IN MONUMENT BOX.

WITNESSES

AZ. 40° CITY OF DETROIT CONTROL MONUMENT 68.22

A7, 1619 48.46 SET PK NAIL WITH W.C.R. TAG IN CONC. CURB

AZ. 222° SET PK NAIL WITH W.C.R. TAG IN CONC. CURB 58.90

AZ. 3430 47.821 SET PK NAIL WITH W.C.R. TAG IN CONC. CURB

THE SELECTED LOCATION IS FOR THIS PROPERTY CONTROLLING MONUMENT IS ACCEPTED AS A CAREFUL AND FAITHFUL DETERMINATION OF THE POSITION INDICATED.

	1200	1	<i>P X</i>
Signed by	11/00	M. C.	Klund

Date

DECEMBER 5, 1995

Surveyor's Michigan License No.

30081