

SURVEY & REMONUMENTATION

APR 25 1995

RC 1515

COMMISSION

LAND CORNER RECORDATION CERTIFICATE Filing Requirement of Act 74, Mich. P.A. 1970

L127797PA677

For corners in

WAYNE (County)

Located In:

Corner Code #

CITY OF SOUTHGATE TWP. #14

1. Public Land Survey

T3S R10E

M-11

T R

T R

T R

2. Property Controlling in Section

S T R

S T R

3. Miscellaneous Property in Sec.

S T R

S T R

Compliance with
ACT 345, P.A. 1990

APPROVED ON: 12-7-94
WAYNE COUNTY REMONUMENTATION
PEER GROUP COMMITTEE

Register of Deeds Stamp & File Number

4. Lot No. , Recorded Plat

5. Private Claims

I, E. PATRICK O'ROURKE, in a field survey on OCTOBER 1, 19 94, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established; re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

ORIGINAL GOVERNMENT SURVEY BY JOSEPH FLETCHER, D.S. 1815-1817

G.L.O. (1816) DESCRIPTION OF CORNER NOT STATED IN NOTES.

WITNESSES: BUSH 12 N 19 E 21 (13.86'R) (GONE)

D.O. 9 S 34 W 9 (5.94'R) (GONE)

RESURVEY AT THE DIRECTION OF ALBERT E. CHAMPNEY, DIRECTOR OF WAYNE COUNTY BUREAU OF TAXATION

W.P.A. (1930's) IRON NORTHWEST 31 (#143)

(CONTINUED ON BACK)

\$ 16.00 MISCELLANEOUS RECORDING

27 DEC 94 11:05 A.M. RECEIPT# 48A

RECORDED

FOREST E. YOUNGBLOOD, REGISTER OF DEEDS
WAYNE COUNTY, MI

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

FOUND 1/2" IRON PIPE IN ROAD BOX AT EUREKA AND BURNS ROADS.

DISTANCE TO L-11 MEASURED AS 2611.41'; RECORD W.P.A. (1930) DISTANCES OF 2611.00' AND 2611.24'

DISTANCE TO B-11 MEASURED AS 2688.06'; RECORD W.P.A. (1930) DISTANCE OF 2688.71'

L.18396 P.327 FOUND 1-1/2" IRON BAR IN CONCRETE MONUMENT BOX WITH COVER (1972) ACT 74 FORM

N 34° W 80.45' PK NAIL IN DETROIT EDISON POLE (MEAS. 80.91')

N 42° E 49.90' PK NAIL IN LIGHT POLE (MEAS. 50.73')

S 50° W 57.05' PK NAIL IN DETROIT EDISON POLE (MEAS. 57.30')

L.18396 P.311 FOUND 1-1/2" IRON PIPE - DISC IN CONCRETE (1973) C.S.

SAME WITNESSES AS L.18396 P.327

L.18859 P.850 FOUND 1-1/2" IRON IN HANDHOLE (1974) C.S.

SAME WITNESSES AS L.18396 P.327

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-11 SECTION CORNER 25,36 T.3S, R.10E

FOUND 1/2" IRON PIPE IN ROAD BOX AT EUREKA AND BURNS ROADS, A FIVE LANE CONCRETE PAVEMENT, AND IT IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.

N 53°13' E 64.62' TIP OF ARROW ON FIRE HYDRANT

N 39°49' E 50.73' FOUND NAIL WITH BRASS TAG IN NORTHWEST SIDE OF UTILITY POLE (SUPRA)

S 49°39' W 57.30' FOUND NAIL WITH BRASS TAG IN NORTHWEST SIDE OF UTILITY POLE (SUPRA)

N 35°03' W 80.91' FOUND NAIL WITH BRASS TAG IN SOUTHWEST SIDE OF UTILITY POLE (SUPRA)

PLACED A REMONUMENTATION BRASS DISC AND PVC CAP #16937 ON ABOVE 1/2" IRON PIPE M-11.

Signed by

E. PATRICK O'ROURKE

Surveyor's Michigan License No. 16937

Date

12-27-94



LI27797PA678

SECTION A (CONTINUED)

WITNESSES: NE 19.61' NAIL EAST SIDE 30" OAK (GONE)
 NE 59.10' HYDRANT (NOW RELOCATED) (MEAS. 64.62')
 SE 67.40' NAIL NORTHEAST SIDE 10" ASH (GONE)
 SW 68.84' NAIL NORTHWEST SIDE 6" TWIN OAK (GONE)
 NW 64.63' NAIL NORTHEAST SIDE 6" ELM (GONE)