

MAR 3 1 1994

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

RECEIVED

1993 DEC -2 PM 3: 51

For corners in
WEXFORD
(County)

Located In:

Corner Code #

Linda Loughmiller
WEXFORD COUNTY, MI
REGISTER OF DEEDS

1. Public Land Survey T 21N R 10W G-13
T R
T R
T R
2. Property Controlling S T R
in Section S T R
3. Miscellaneous S T R
Property in Sec. S T R
4. Lot No. , Recorded Plat
5. Private Claims

Register of Deeds Stamp & File Number

I, CRAIG J. PULLEN, in a field survey on OCTOBER 13, 1993, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

G-13 1837 GLO SURVEY WOOD POST BEECH 8" N14½°W 25.74' BEECH 8" N44½°E 15.84'
1989 SURVEY BY P. LEEMON, PS #31595, RECORDED IN L.4, P.49. SET 2" X 30" I.P. WITH BRASS CAP FROM GLO EVIDENCE J. PINE 8" N78°E 106.19' J. PINE 7" N49°E 106.25' W. PINE 7" N9°E 135.30' P. POST W 1.0'

B. Description of corner evidence found and/or method applied in restoring or reestablishing corner:

G-13 FOUND 2" X 30" I.P. WITH BRASS CAP AND WITNESSES FROM L.4, P.49. THIS CORNER IS ACCEPTED AS A CAREFUL AND FAITHFUL PERPETUATION OF THE POSITION OF THE ORIGINAL CORNER.



C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

G-13 SW CORNER OF SECTION 34, T21N, R10W
2" X 30" I.P. WITH U.S.F.S. BRASS CAP
N78°E 8" JACK PINE 106.19'
N49°E 7" JACK PINE 106.25'
N9°E 7" WHITE PINE 135.30'
WEST 4" X 7" PINE POST 1.0'

Peer Group Reviewed and Approved

Date: Nov 29, 1993

Richard D. Wilcox, Wexford County Surveyor

Signed by Craig J. Pullen

Date NOVEMBER 23, 1993

Surveyor's Michigan License No. 39095