LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF –:	LOCATED IN –:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. ●., R. 10 ●. W.	C-9, D-9, E-9
2. PROPERTY CONTROLLING IN SECTION 29	,T. 24 N. ●., R. 10 ●. W.	1, 2
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Sept. 27, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19__, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (continued)

1

Fd. 1" pipe, set Ced.Post w/Loc.Tag

18" Oak	S42°W	93.4
17" Oak	N22°W	103.5
5" Oak	S50°E	62.6

2

Fd. 1" pipe & Ced.Post; Set Ced.Post w/Loc.Tag

10" Twin R.Oak	N74°W	91.4
9" Maple	N82°E	36.4
11" Maple	S44°E	52.4
N-S Trail rd.	Due W.	170'±

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-9 Fd. Dept. Mon. (1962) which perpetuates Schaaf Mon.(1938) who had original evidence.

D-9 Fd. Dept. Mon.(1962) as established by S.P.

E-9 Fd. Dept. Mon.(1962); which perpetuates Schaaf Mon.(1938) who had orig. evidence.

1 Fd. 1" Pipe from previous Dept. Survey (1962) as estab. by S.P.

2 Fd. 1" pipe from Dept. Survey (1962) as estab. S.P.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-9

Fd. Dept.Mon., Set Ced.Post

15" R.Pine	N64°W	142.3'
12" R.Pine Stub	S12°W	49.4'
9" Cherry	N72°E	111.5'

D-9

Fd. Dept. Mon.Set Ced.Post

19" R.Pine	N02°W	96.2
17" R.Pine	S62°E	92.4
26" Oak	N58°W	73.4

E-9

Fd. Dept. Mon.&Ced. Post

18" W.Pine stp.	N18°W	47.4
20" W.Pine stp.	N89°E	48.1
8" Triple Maple	N62°W	129.8

Cor. fn. Post (down)
Fn's. w'1/y & S'1/y,23'-W&14'-N.

SIGNED BY Carl F. Roser 10-2-78 DATE _____

STATE OF MICHIGAN CARL F. ROSER (SEAL) LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ (CHIEF OF SURVEY PARTY) DATE _____

APPROVED AND SIGNED BY _____ (MICHIGAN REGISTERED LAND SURVEYOR) DATE _____ (SEAL)

GREENWOOD TOWNSHIP
WEXFORD COUNTY

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET