LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF—:	LOCATED IN—:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY	T. 24 N. S., R. 10 E. W.	C-10; C-11
2. PROPERTY CONTROLLING IN SECTION 29	,T. 24 N. S., R. 10 E. W.	3; 5; 10
3. MISCELLANEOUS PROPERTY IN SECTION	,T. N. S., R. E. W.	
4. LOT NO. , RECORDED PLAT		
5. PRIVATE CLAIMS		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on Sept. 27, 1978, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

C. (continued)

5

Set 5/8"X40" re-rod w/plastic RLS Cap & Ced. Post w/Loc. Tag

5" Maple	S24°W	24.9
5" Maple	S52°E	11.0
4" Oak	N48°E	14.4

Fd. Conc. Mon
S86°37'E 10.66

10

Fd. 1" pipe, set Cedar Post w/Loc.Ta

11" R.Pine	S36°E	12.6
7" R.Pine	N82°W	7.8
4" Maple	N46°E	20.4

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

C-10 Fd. Dept. Mon.(1962) which perpetuates Schaaf Mon.(1938) who had original evidence.

C-11 Fd. Dept. Mon.(1962) which perpetuates Schaaf Mon. (1938) who had original evidence.

3 Fd. 1" Pipe as estab. in previous Dept. Survey (1962) by S.P.

5 Established 1/8 Cor. per standard B.L.M. Instructions.

10 Fd. 1" pipe from previous Dept. Survey (1962) as estab. by S.P.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

C-10

Fd. Dept.Mon,SetCedar Post

13" R.Pine	N32°W	18.0
20" R.Pine	S52°W	23.9
9" Tw.Maple	N36°E	14.5

C-11

Fd. Dept.Mon.& Ced.Post

8" Maple	S40°E	21.0
8" Maple	S14°E	38.1
8" Maple	S71°W	46.7
5" R.Pine	N83°W	52.2

3

Fd. 1" pipe,set Ced.Post w/Loc.Ta

20" Tw.Oak	N45°W	16.8
9" R.Pine	N74°E	60.4
4" Oak	S21°E	27.5
E-W Trail Rd.	Due N	60'±

SIGNED BY Carl F. Roser 10-2-78 DATE

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

STATE OF MICHIGAN SEAL CARL F. ROSER LAND SURVEYOR No. 12028 REGISTERED LAND SURVEYOR

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____ DATE _____
CHIEF OF SURVEY PARTY

APPROVED AND SIGNED BY _____ DATE _____
MICHIGAN REGISTERED LAND SURVEYOR

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

GREENWOOD TOWNSHIP
WEXFORD COUNTY

FORM APPROVED BY MICHIGAN STATE BOARD OF REGISTRATION, JAN. 28, 1971
REVISED MAY 14, 1975

MAY PLACE SKETCH ON BACK OR ATTACHED SHEET