

**LAND CORNER RECORDATION CERTIFICATE**  
**FILING REQUIREMENT OF ACT 74, MICH. P.A.1970**

FOR CORNERS OF--:	LOCATED IN--:	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. 24 N. R. 10 W. ●	M-2; M-3; M-4
2. PROPERTY CONTROLLING IN SECTION_____	T. _____ N. S. R. _____ E. W.	
3. MISCELLANEOUS PROPERTY IN SECTION_____	T. _____ N. S. R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND  
FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on November 14, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on \_\_\_\_\_, 19\_\_\_\_, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. Description of original monument and accessories and/or subsequent restoration:

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- M-2** Fd. Fargo (1913) butter dish & stake bottom shadow from Fargo witness showing scribe marks. Fargo notes indicate they had an original corner.
- M-3** Reestablished SE corner Sec. 1 (24-10) equidistant & on line between found Fargo  $\frac{1}{4}$  corners  $\frac{1}{2}$  mile to N & S. While setting corner, fd. Fargo stake shadow, lime remains & pine stump witness remains S16 $\frac{1}{2}$ °W. Corner falls in mature red pine plantation.
- M-4** Found Fargo 1" pipe & one witness for  $\frac{1}{4}$  corner common to Sec. 12, T24N-R10W, and Sec. 7, T24N-R9W.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

M-2	M-3	M-4
Fd. Fargo corner; replaced w/ std. Wex. Co. mon. & cedar post w/loc. tag.	Set Wex. Co. mon. & cedar post w/loc. tag.	Fd. Fargo mon.; replaced w/Wex. Co. mon. & set ced.post w/loc. tag.
10" Cedar N66°W 20.3	6" R. Pine N35°E 7.2	*18" Twn.Cedar N85°E 13.9
8" Maple S23°W 15.7	8" R. Pine N80°W 3.4	21" Twn.Cedar S55°W 17.2
7" Maple N33°E 14.3	6" Twn. R. Pine S30°E 8.7	17" Cedar N40°W 15.2
Q. N-S trl. rd. Due E 97'±		* = Fargo witness
N-S random Due W 37'±		

SIGNED BY Carl F. Roser

DATE 1-30-80

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY \_\_\_\_\_

CHIEF OF SURVEY PARTY

DATE \_\_\_\_\_

APPROVED AND SIGNED BY \_\_\_\_\_

MICHIGAN REGISTERED LAND SURVEYOR

DATE \_\_\_\_\_

(SEAL)

SURVEYOR'S MICHIGAN REGISTRATION NO. \_\_\_\_\_

GREENWOOD TOWNSHIP  
WEXFORD COUNTY