

LAND CORNER RECORDATION CERTIFICATE

FILING REQUIREMENT OF ACT 74, MICH. P.A.1970

FOR CORNERS OF--	LOCATED IN--	CORNER CODE NUMBER
1. PUBLIC LAND SURVEY_____	T. 24 N. R. 10 W.	L-1; L-3; M-1
2. PROPERTY CONTROLLING IN SECTION_____	T. 24 N. R. 10 W.	8
3. MISCELLANEOUS PROPERTY IN SECTION_____	T. _____ N. R. _____ E. W.	
4. LOT NO. _____, RECORDED PLAT _____		
5. PRIVATE CLAIMS _____		

REGISTER OF DEEDS STAMP AND FILING NUMBER

I, Carl F. Roser, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were, in a field survey on December 11, 1979, established, re-established, monumented, re-monumented, recovered or restored as expressed below and in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a court of law. Furthermore, that the corner points mentioned in lines 3, 4 and 5 above were, in a field survey on _____, 19____, found, recovered, restored, established or re-established as expressed below and in conformance with the rules of the Michigan State Board of Registration for Land Surveyors or, by a Decree of a Court of law:

A. - Description of original monument and accessories and/or subsequent restoration:

C. (continued)

8
Drove 5/8"x36" rerod w/RLS cap &
set cedar post w/loc. tag.
4" Cedar N50°E 16.2
5" Cedar S75°E 25.3
6" Cedar N42°W 40.0

B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

- L-1 Fd. 2" Schaaf pipe, 18" above ground & 1" Fargo pipe (1913) along side same & one Fargo pine stump (scribed) SE for 1/4 corner common to Sec. 1 T24N-R10W, Wexford Co. & Sec. 36, T25N-R10W, Grand Traverse County.
- L-3 Fd. Fargo pipe & butter dishes (1913), replaced with Wexford County monument.
- M-1 Fd. Fargo butter dish & Schaaf monument for corner common to T24 & 25N-R9 & 10W. Road (in curve) to N & E is N45°E 30±'.
- 8 Set 1/8 corner per standard B.L.M. instructions.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

L-1	L-3	M-1
Fd. 2" pipe & set ced.post w/ loc. tag.	Fd. Fargo corner; replaced w/ std. Wex. Co. mon. & ced.post.	Fd. Schaaf pipe & Fargo butter dish; replaced w/std. Wex. Co. mon. & cedar post w/loc. tag.
8" Maple N58°W 29.5	6" Maple N70°W 62.8	12" R. Pine N58°W 34.4
12" Maple N62°E 26.2	3" W. Pine S60°E 4.5	9" Cedar N57°E 78.0
5" Maple S72°E 12.0	10" Cedar S58°W 50.7	13" Maple S20°E 74.7
18" W.Pine Stump S77°E 46.2	9" Cedar S82°W 18.5	

(scribed - Fargo)

SIGNED BY Carl F. Roser

DATE 1-30-80

SURVEYOR'S MICHIGAN REGISTRATION NO. 12028

FOR STATE AND UNITED STATES AGENCIES:

SIGNED BY _____

DATE _____

APPROVED AND SIGNED BY _____

DATE _____

SURVEYOR'S MICHIGAN REGISTRATION NO. _____

GREENWOOD TOWNSHIP
WEXFORD COUNTY

