

LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. PA 1970

For Corners In:
Wexford
(County)
Located In
Corner Code #
1. Public Land Survey
2. Property Controlling in Section
3. Miscellaneous Property in Section
4. Lot No:
5. Private Claims:

I, Craig W. McVean, in a field survey on June 28, 2005 do hereby state that under requirements of PA 74, Michigan PA of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by a decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by a Decree of a Court of Law; established, re-established, monumented, recovered, found as expressed below:

NOTE: Not more than 2 corners, all in the same town and range, may be recorded on this certificate.

A. Description of original monument and accessories and/or subsequent restoration:

10 - None
11 - None



B. Description of corner evidence found and/or method applied in restoring or re-establishing corner:

10 - S 1/16 Cor. common to Sec. 16 & 17 - Set stamped 2" Alum. Cap on 5/8" x 34" iron rebar per standard BLM procedure.
11 - SW 1/16 Cor. Sec. 16 - Set stamped 2" Alum. Cap on 5/8" x 34" iron rebar per standard BLM procedure.

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

10 - 2" Alum. Cap on 5/8" x 34" rebar
Set Blue Carsonite Post with loc. tag 1' N.
S55°W 29.60' to set N & T in SE side 4" R. Pine
N45°W 51.58' to set N & T in NE side 14" R. Pine
N38°E 44.18' to set N & T in NW side 14" R. Pine
N2°E 36.60' to set N & T in W. side 16" R. Pine
11 - 2" Alum. Cap on 5/8" x 34" rebar
Set Blue Carsonite Post with loc. tag 1' NE
N15°W 26.86' to set N & T in W. side 8" R. Pine
N60°E 73.26' to set N & T in SW side Tri. 14" R. Maple
S10°E 18.34' to set N & T in W. side 12" J. Pine
N66°W 47.85' to set N & T in N. side 11" R. Pine

Signed by: [Signature] Date: 6/7/2006
Surveyor's Michigan License No.: 39088