

REMONUMENTATION
LAND CORNER RECORDATION CERTIFICATE
Filing Requirement of Act 74, Mich. P.A. 1970

For corners in
Washtenaw
(county)

Located in

Corner Code #

TIME RECORDED 9:23 AM
DATE Feb 18 1997
PEGGY M. HAINES
WASHTENAW COUNTY CLERK/REGISTER

1. Public Land Survey T 2S R 7E I-11
T _____ R _____
T _____ R _____
T _____ R _____
2. Property Controlling S T R _____
in Section S T R _____
3. Miscellaneous S T R _____
Property in Sec. S T R _____

Liber 00001 Page 0677

Register of Deeds Stamp & File Number T3M

4. Lot No. _____, Recorded Plat _____
5. Private Claims _____

I, R.T. Tietsema, in a field survey on July 30, 19 96,
do hereby certify that under the requirements of P.A. 74, Michigan P.A. of
1970, the corner points mentioned in lines 1 and 2 above were in
conformance with the regulations and rules therefore as required in the
current manual of survey instructions of the United States Department of the
Interior, Bureau of Land Management of by a decree of a Court of Law and/or
that the corner points mentioned in lines 3, 4, and 5 above were in
conformance with the rules of the Michigan Board of Land Surveyors or by a
Decree of a Court of Law; established, re-established, monumented,
recovered, found as expressed below.

	A	B	C	D	E	F	G	H	I	J	K	L	M
2	6	5	4	3	2	1							
3													
4	7	8	9	10	11	12							
5													
6	18	17	16	15	14	13							
7													
8	19	20	21	22	23	24							
9													
10	30	29	28	27	26	25							
11													
12	31	32	33	34	35	36							
13													

NOTE: Not more than 4 corners, all in the same town and range, may be
recorded on this certificate

A. Description of original monument and accessories and/or restoration:

Set post Corner of Sections 26, 27, 34, & 35 1819 GLO (Wrangler) Fld. Notes	Set Original Corner	1) 28" Hickory S71W 2) 34" White Oak S80E	16 Links (10.56') 43 Links (28.38')
1922 J. Lovell Resurvey (grid book)	4" Tile, 1 1/2" Iron Pipe, Brick and Stones (from A-H dvw. compiled by Armstrong in 1959, dwg# 242-53).	3) NW Cor. of Well S48 1/2E 4) 6" Elm N74E 5) 18" B. Walnut S4E 6) 14" B. Walnut S8W 7) 14" Elm N69W 8) 8" Basswood N32 1/2E	47.2' 84.0' 249.0' 148.1' 92.5' 67.3'

(continued on back)

B Description of corner evidence found and/or method applied in restoring or reestablishing corner:

Found Rod in Mon. Box.

Also found remaining witnesses

10) D.E. pole	N75E	80.50'
12) M.B.T. pole	S40W	74.80'
13) D.E. & M.B.T. pole	N65W	49.20'

C Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 1" Pipe and Remonumentation Cap.

Set additional accessories:

10) Utility Pole	N75E	80.61' to nail & R.T.
12) Utility Pole	S29W	74.90' to nail & R.T.
13) Utility Pole	N63W	48.99' to nail & R.T.
14) 27" Basswood	N31E	67.00' to nail & R.T.
15) 18" Walnut	S7W	148.31' to nail & R.T.
16) Conc. Mon.	S34E	73.36' to nail & R.T.

SURVEY &
REMONUMENTATION

MAY 05 1997

COMMISSION

It is our opinion that this corner represents the original corner and is accepted as the best available evidence of the position of the original corner.

Signed by

R. T. Tietsema
Surveyor's Michigan License No. 20712

Date DEC 02 1996

FORM APPROVED BY MICHIGAN STATE BOARD OF LAND SURVEYORS, JAN. 28 1971
REVISED MAY 14, 1971
REVISED JAN., 1981

APPROVED

DATE 9/23/96

CO. REF. KA

COPY

1/22/1959	W. J. Armstrong (Atwell-Hicks)	Compiled Surveys Dwg. #242-53	4" Tile, 1 1/2" Iron Pipe, Brick and Stone.	3) NW Cor. of Well 4) 6" Elm 5) 18" B. Walnut 6) 14" B. Walnut 7) 14" Elm 8) 8" Basswood	S48 1/2E N74E S4E S8W N69W N32 1/2E	47.2' 84.0' 249.0' 148.1' 92.5' 67.3'		
12/13/1977	Francis A. Papke	9675	L4P376	Unknown Fnd. 1 1/2" Iron Pipe (Installed cast iron box in asphalt pavement)	9) 20" B. Walnut 10) D.E. Pole 11) Dead-Man pole 12) M.B.T. pole 13) D.E. & M.B.T. pole	N35E N75E S60E S40W N65W	66.85' 80.50' 61.10' 74.80' 49.20'	set nail W. side set nail N. side set nail S. side set nail W. side set nail S. side
1/10/1991	Michael L. Millett	29249	L7P265	Unknown Fnd. Rerod in Man. Box	10) D.E. Pole 11) Dead-Man pole 12) M.B.T. pole 13) D.E. & M.B.T. pole	N75E S60E S40W N65W	80.50' 61.10' 74.80' 49.20'	nail N. side nail S. side nail W. side nail S. side