

A circular professional seal for a surveyor in the State of Michigan. The outer ring contains the text "STATE OF MICHIGAN" at the top and "LICENSED PROFESSIONAL SURVEYOR" at the bottom, separated by two stars on each side. The inner circle contains the name "KENNETH R. COLEMAN", the title "PROFESSIONAL SURVEYOR", and the license number "No. 37271". The seal is stamped in black ink on a document.

"A" continued...

11-1887 C.S. Woodard

Woodard's notes

Stake stones and brick.

3) 20" W. Oak	N9°W	118.2
4) 20" B. Oak	S30½°W	39.6

7-9-38 W.J. Armstrong

Grid book

Found old wood stake, stones and bricks. Set 1½" X 36" iron pipe.

Left stones and brick as found.

5) 30" B. Oak	N28°E	76.7
6) 4" Butternut	N53½°E	39.4
7) 2" Butternut	N87°E	32.9
8) 2" Butternut	S80½°E	30.9
9) 10" B. Oak	S32½°W	26.8
10) 10" W. Oak	N36½°W	28.9
11) 7" B. Oak	N11°W	52.8

3-7-74 Atwell-Hicks, Inc.

Field book 782-20

Found 1" I.P. W. edge road.

5) 46" Oak	N30°E	76.80 nail
12) 24" Oak	N6°W	88.45 nail
13) N.E. cor. sq. block pillar	W'ly	32.44
14) 40" Oak	S20°E	95.70 nail

8-16-76 Roskelly, Jekabson & Assoc.

Survey

Found iron bar.

8) 12" B. Walnut	S80°E	30.70 nail
9) 24" R. Oak	S10°W	26.20 bolt
12) 24" R. Oak	N10°W	88.45 nail
15) I.P.	WEST	33.00
16) W 1/4 cor. sec. 30 I.P.	NORTH	188.18

6-77 Control Survey Assoc.

Survey

Found 1½" I.P.

5) 30" B. Oak	N28°E	76.7
7) 5" Walnut	N87°E	32.9
8) 4" Walnut	S80°E	30.9
9) 15" B. Oak	S32°W	26.8

4-5-79 Washtenaw Engineering Co.

LCRC L.5, P.210 &
Survey L.1702, P.363

Found 1½" I.P.

5) 36" B. Oak	N28°E	76.7
7) 8" Butternut	N87°E	32.9
8) 10" Butternut	S80½°E	30.9
9) 24" B. Oak	S32½°W	26.8
10) 24" W. Oak	N36½°W	28.9
11) 26" B. Oak	N11°W	52.8
13) N.E. cor. block pillar	S89°W	32.40

"C" continued...

1-24-1995 Atwell-Hicks, Inc.

Remon.

Found 1½" I.P. 0.9' below gravel surface. Placed remon. witness tag and top of yellow cap #37271 on top center of pipe. Drove 3" concrete nail into pipe.

5) 38" B. Oak	N28°E	76.76 nail & R.T.
7) 12" Butternut	N87°E	33.12 C.L. tree
8) 14" Butternut	S80½°E	30.78 nail & R.T.
9) 24" B. Oak	S32½°W	26.56 nail & R.T.
10) 24" W. Oak	N36½°W	28.38 nail & R.T.
11) 30" B. Oak	N11°W	52.54 C.L. tree
12) 26" Oak	N6°W	88.34 nail
13) NE cor. sq. block pillar	W'ly	32.26
15) 3/4" I.P.	W'ly	33.00
16) A-10 Ypsilanti Township	NORTH	188.08

APPROVED

DATE 4/24/95

NO. REP. KX