

SURVEY &  
REMONUMENTATION

COPY

RECORDED  
WASHTENAW COUNTY, MI

MAY - 1 1995

LAND CORNER RECORDATION CERTIFICATE

FEB 1 8 52 AM '95

COMMISSION

Filing Requirement of Act 74, Mich. P.A. 1970

For corners in

WASHTENAW

(County)

Located In:

Corner Code #

1. Public Land Survey

T 4 S R 4 E

M-9

2. Property controlling  
in Section

S

T

R

3. Miscellaneous

S

T

R

Property in Sec.

S

T

R

4. Lot No. , Recorded Plat

5. Private Claims

PEGGY M. HAINES  
COUNTY CLERK/REGISTER

- COPY -

LIBER

1 PAGE 356 RM

COPY

Register of Deeds Stamp & File Number

I, Paul V. Schwimmer, in a field survey on September 29, 19 93, do hereby certify that under requirements of P.A. 74, Michigan P.A. of 1970, the corner points mentioned in lines 1 and 2 above were in conformance with regulations and rules therefore as required in the current manual of survey instructions of the United States Department of the Interior, Bureau of Land Management or by decree of a Court of Law and/or that the corner points mentioned in lines 3, 4 and 5 above were in conformance with the rules of the Michigan Board of Land Surveyors or by Decree of a Court of Law; established, re-established, monumented, re-monumented, recovered, found as expressed below:

NOTE: Not more than 4 corners, all in the same town and range, may be recorded on this certificate

A. Description of original monument and accessories and/or subsequent restoration:

Set Wood Post, Feb. 24, 1816, GLO

(1) W. Oak 16' S 7' 34 links

(2) W. Oak 12' N 23' W 22 links

Found 1" Iron Pipe surrounded by stones

(3) 18" Hickory N 4'E 14.4'

(4) Twin 6" Crabapple South 30.5'  
Centerline Willow Road extended and on  
N&S tree row

Jack N. Owens LS 20709

Atwell-Hicks, Inc

11/28/73

LCRC L3, P329 & Survey

Found 1" Iron Bar

(5) 6" Ash N 70' W 8.70'

(6) 8" Twin Cherry S 30' W 4.50'

(7) 18" Hickory South 40.30'

(8) NW Corner Section 30, T4S, R5E South 61.38

I. John Jekabson LS 19836

Roskelly, Jekabson & Assoc.

9/6/83, Survey Job #83-7-135

Field notes from survey indicate the corner used by Owens was the corner to sections 19 & 30 of Saline TWP. The Owens corner appear to be on line with Willow Rd. to the East.

B. Description of corner evidence and/or method applied in restoring or reestablishing corner:

Found 1" Iron Bar in stones

(5) 8" Ash East 8.7'

(8) NW Corner Section 30, T4S, R5E 61.38'

C. Description of monument for corner and accessories established to perpetuate locating the position of the corner:

Set 2" aluminum remonumentation cap over existing 1" iron bar

(9) Set nail w/ RT on S. side of (5) 8" Ash East 8.67'

(10) Set nail w/ RT on E. Side of 18" Hickory North 113.78'

I believe this point should be accepted as the best available evidence of the original corner.



Signed by

Paul V. Schwimmer

Date

12/29/94

Surveyor's Michigan License No.

24618

APPROVED

DATE 12/19/94

CO. REP. LA